




MERICAN

[Entered at the Post Office of New York, N. Y., as Second Class Matter. Copyright, 1910, by Munn & Co., Inc.]

A POPULAR ILLUSTRATED WEEKLY OF THE WORLD'S PROGRESS

Vol. CIII. -No. 24. ESTABLISHED 1845. NEW YORK, DECEMBER 10, 1910.

10 CENTS A COPY. \$3.00 A YEAR.



Thousands of dollars converted into smoke by a carelessly used match.

procedure. Unfortunately, the New York navy vard

SCIENTIFIC AMERICAN

ESTABLISHED 1845

MUNN & CO., Inc., - Editors and Proprietors

Published Weekly at No. 361 Broadway, New York

CHARLES ALLEN MUNN, President fill Broadway, New York. FREDERICK CONVERSE BEACH, See y and Tr fill Broadway. New York.

TERMS TO SUBSCRIBERS	
Subscription one year.	\$3,00
Postage prepald in United States and possessions	
Mexico, Cuba and Panama,	
Postage to Foreign countries	

THE SCIENTIFIC AMERICAN PUBLICATIONS. ilie American (establishut 1845) ilie Xinerican Southwinent (established 1876) can Homes (not Gardens) . . \$5.00 a year tomes and Fardens 3.0
sined subscription falcs and rates to foreign countries,
who be furnished upon application. ress money order, or by bank draft or check.

MUNN & CO., Inc., 861 Broadway, New York

NEW YORK, SATURDAY, DECEMBER 10th, 1910.

subjects of timely interest. If the contributions will ort, and the facts authentic, the contributions will ention. Accepted articles will be paid for at regular st

THE FORTHCOMING GERMAN ANTARCTIC EXPEDITION

T is expected that the German Antarctic expedition under Lieut, Filchner will leave Germany in the early spring of 1911. Half the expenses of the expedition, estimated at 1,200,000 marks have been subscribed, and the whaling-ship "Björn, has been purchased and renamed the nd." The crew will number 25, under icetons. pilot Jörgensen, and the following, in addition to Filchner, will constitute the scientific staff: Dr. Barof the Potsdam Meteorological Observatory meteorologist and physicist; Dr. Brennecke, of the Deutsche Seewarte, oceanographer; Dr. Heim, geologist; Dr. Kohl, surgeon; Dr. Pryzbyllok, of the Potsdam Geodetic Observatory, astronomer and magneti-cian; Dr. Seelheim, geographer; Herr Neuberger, techgist; and another surgeon, not designated.

On its way southward the expedition will make a series of oceanographic observations in the Sargass Sea and the Brazil Current, the intention being to explore a more westerly region of the Atlantic than has been investigated by previous expeditions. It is cted to enter the ice at South Georgia and proce thence to the Sandwich Group, and then advance south ward into Weddell Sea. A base station is to be estab-lished on the mainland south of Coats Land, from which the sled expeditions will start. It is expected that Captain Scott's English expedition will, in the have entered the Antarctic regions fro the opposite side; i. e., from Ross Sea. In case the ditions meet, as Fiichner confidently expe will, part of the German party will turn back and Scott to Weddell Sea, and se English will retrace their steps, to guide Filchner ward to Ross Sea, each expedition thus making use of the provision-depots established by the other.

The proposed Scottish expedition, under Bruce, also expects to enter the pelar regions by way of Weddell but has agreed to confine its operations portion east of longitude 20 deg., while the German party will remain west of that line. There is, of course, a possibility that all three expeditions may where in the heart of the Antarctic

The work at the base-station will include continuous meteorological and magnetic observations, including aerological investigations with kites and pilot-balloons These will be of especial interest owing to the proximity, to the northward, of the meteorological stations maintained by the Argentine government in the South Orkneys and South Georgia.

RAPIDITY IN WARSHIP CONSTRUCTION.

HEN the House of Representatives recently passed the bill for naval appropriations, they stipulated under the heading "In-crease of the Navy" that of the two battleships authorized one or both might be built in a United States navy yard. Owing to the inclusion in the act of a clause calling for an eight-hour day for all workmen employed on these vessels, it looks as if the Navy Department might itself have to under take the construction of both ships, for several of our shipyards—notably the Fore River Iron Works announce that they could not afford to bid under such conditions. Only one shipbuilding company (the Newport News yard) submitted bids for a battleship. The four optional tenders sent in ranged from \$5,760,000

There are numerous reasons which might be advanced why it would be highly inexpedient to have both ships built by the government, but chief among these is the delay that would ensue from such a

is the only one in the country which has the facilities for building large armored ships, and even at New but one can be built at a time. at this date fairly well on the road toward completion, is in the water, so that her slip is available; but many valuable months would undoubtedly be lost before Capt. Baxter (the naval constructor in cnarge) could erect another slip and the accompanying plant for the second battleship. In these days of mad rivalry among the leading nations of the world for the mastery of the sea, the necessity for speedy

construction is apparent; and with our conservative programme of but two new capital ships a year, we cannot afford to allow too much time to elapse between the letting of contracts and the delivery the vessels to the government. Hence it is probable that the wise heads in Washington will find some means to accomplish the building of one of the two

ships in a private yard.

Until about six years ago it was a standing reproach to our naval administration that they showed so much leniency toward the private concerns in the matter of living up to the letter of their contracts, especially the clause regarding rapidity of construc-The bidders, when submitting proposals, were required to state the length of time it would take them to complete the ships for delivery to the govern-(It might easily happen that, other conditions ment. being equal, this one factor might determine the award of the contract.) Nevertheless, the time clause was pretty generally ignored, so that frequently ships not ready for sea five years after being laid. Indeed, instances are not lacking of government work being practically suspended, so that some merchantman might be hurried to completion.

When Mr. Roosevelt became President, he displayed keen personal interest in the affairs of the navy and wherever he found abuses he took prompt steps to put an end to them. In 1902 the "Maine," "Misand "Ohio" were still in the builders' hands though they had been authorized as far back as 1898; and of the five powerful vessels of the "New Jersey class, not one was making satisfactory progress. new fleet, which Congress had so generously provided for in the years subsequent to the Spanish war, was still mostly on the stocks, and things in general were languishing, when Mr. Roosevelt, seeing at once where the trouble lay, applied the proper remedy. was needed was competition. Not competition alone between the various yards, but outside competition So in a message to Congress he recommended that they include in the naval bill, which that year authorized the construction of two battleships, a provision that the Secretary of the Navy might, at his discre tion, build one of them at a government navy yard This he did, and the results which followed trans-cended expectations. The "Connecticut," of 16,000 tons, was laid down in the New York navy yard; the contract for her sister, the "Louisiana" being awarded to the Newport News Ship Building and Dry Dock Company. Forced thus to compete with the United States government, the Newport News people be-stirred themselves, and bent every energy toward finishing the "Louisiana" ahead of her rival.

The "Connecticut" was heavily handicapped at the start, pending the erection of the necessary cranes and shops and the building of a slip; but Naval Constructor Baxter, to whom this important task was intrusted, bravely overcame all obstacles, and set a pace which gave the private yard all it could do to And this despite their added advantage keep up. being able to work their men ten hours a day to the government's eight. When the "Connecticut" was about two-thirds completed, however, work on her had to be suspended to await the delivery of her armor plate, of which she carries about four thousand tons. She was launched just eighteen months after her keel was laid, thus tying the "Louisiana's" record. latter, though, was the first to go into commiss only three years and three months after her keel plates were placed upon the ways. This performance provto the entire satisfaction of the authorities that with sufficient incentive our shipyards could turn out a battleship within a reasonable time; and Congress, acknowledging the success of the experiment, has since most of its naval bills a provision giving the Secretary of the Navy power to build battleships at government yards should he deem it advisable. He did not exercise this privilege, however, until two ago, for the private concerns have lately managed to turn out our ships in even less than the con-

In 1908 the Secretary ordered the huge dreadnought to be laid down at the New 21,500 tons. York yard, where Constructor Baxter had a splendidly drilled force of workmen putting the finishing touches on the new fleet collier "Vestal," of 12,500 tons, which had then recently left the ways. The "Florida's" sister ship, the "Utah," is being built by the New York Shipbuilding Company, of Camden, N. J., and the rivalry between the two leviathans is even keener than that of the "Connecticut" and "Louisiana." Though these "super-dreadnoughts' are 5,500 tons larger than the older vessels, so great has been the improve building methods in the intervening few years, that the "Utah" was launched in ten months, 58 per cent completed, while the "Florida" left the ways in fourteen months with 631/2 per cent of the work done. It is expected that both of these mighty vessels will be in commission within two years after they were laid down.

We have now about reached the point where the rgest man-of-war may be built quite as quickly on largest this side of the Atlantic as anywhere in the world, except possibly in England. Germany, urged by her who has made the Fatherland's new navy special hobby, has so improved her dockyard facilities in the last two or three years, that she can turn out dreadnoughts in from twenty-four to twenty-seven months. France still requires a full three years, and Japan at least that long. In England, the home of steel ships, there are several yards, both government and private, where a dreadnought may be built in a year and a half if necessary. The original ship of that name (that is, the present "Dreadnought") was launched in less than five months, and delivered one year and one day after her keel was laid down. This remarkable and unequaled record was made at the Portsmouth (Admiralty) dockyard in 1905-6,

In the list given below will be found the time it took to complete our newer battleships (those at present composing our Atlantic fleet), and the reader tice the sudden acceleration which ensued after government competition had taught the private builders that the navy wanted its ships to sail with the fleet, and not to ornament the stocks in a shipyard

Builder. Displacem't, Yrs. Mths Name. New Jersey Fore River I. W. 15,000 Georgia . Bath Iron Works 15,000 Georgia Bath Iron Works Rhode Island Fore River I. W. 15,000 9 Virginia ... Newport News S. B. Co. . Moran Bros. Nebraska . 15.000 Louisiana. Newport News S. B. Co. Connecticut.....N. Y. Navy Yard 16,000 Minnesota. . Newport News S. B. Co. Vermont.......Fore River I. W. Kansas.....N. Y. Shipbuilding Co. 16,000 9 IdahoCramps 13,000 10 Mississippi New Hampshire, N. Y. Shipbldg, Co. 16,000 10 South Carolina Cramps
Michigan N. Y. Shipbldg. Co.
North Dakota Fore River I. W. 16,000 Delaware... Newport News S. B. Co. 20,000

IMMUNITY IN PLANTS.

INCE plants have nothing that corresponds with the blood corpuscles, the conclusion was reached by many botanists that the principle of phagocytosis had no application to the But now the French botanist, Prof. Bernard, of the University of Caen, has pointed out analogy between the process described by Metchnikoff and a process that takes place in certain

Most of the diseases of higher plants are caused. by bacteria or protozoans, but by filamentous fungi, related to the molds. In the roots or underground stems of many of the higher plantsall the species of the orchid family, the heath family and many others-there is always present a colony of such fungi. The presence of the fungus does not seem to cause permanent injury to the plant, but does seem to be of any use to the plant either. Many theories have been advanced as to the significance of this association or symbiosis between the higher plant and the fungus. Prof. Bernard points out that some of these fungi are known to cause diseases in certain plants, and infers that in the orchids, for example, they produce no injury, because when the fungus has penetrated into the interior of the cells, the protoplasm of the latter begins to digest it, in the same way as the white corpuscles of our blood digest invading bacteria

This view is supported by the fact that there is progressive degeneration of the fungus within the cells of the host in practically all such associations that have been examined. By means of careful experiments, Dr. Bernard has further shown that in a given orchid a certain fungus will do no harm whatever, being digested and reduced to dead clumps, whereas closely related species of fungi will act in every way like disease-producing invaders.

He concludes that while plants have no moving cells corresponding to the plagocytes of animals that are capable of attacking and devouring invaders, many of the cells in most plants still retain, to a certain extent, the ability to digest any invaders that may get into them. To the extent that this ability is retained the plants will be immune from disease. This brings the cerious mycorhiza or root fungus into harmony wit! Metchnikoff's theory of immunity

Scientific American

ELECTRICITY.

Our consul at Zanzibar, Africa, calls attention to the increasing use of wireless telegraphy in Africa, and suggests that manufacturers of wireless apparatus should look into this promising field. There are five stations now at Benardir, Zanzibar, and Pemba, and it is planned to establish stations in British East Africa and German East Africa.

The use of the telephone for dispatching trains is meeting with success in New England. A hundred miles of the New York, New Haven and Hartford Railroad is equipped with the telephone system. On the Boston and Maine Railroad the White Mountain division and the Concord division are thus equipped. The main line of the Boston and Albany Railroad has 165 telephone stations, while the Central Vermont Railroad is about to install telephone service on the division from St. Albans to Windsor.

A record transmission voltage for Europe will be stablished by the Lauchhammer power station in Germany, which will transmit power at 110,000 volts. The different works of Messrs. Lauchhammer, Ltd., have heretofore been supplied from separate power Finding that their works at Lauchhammer were situated on a rich lignite field, it was decided build a central power plant to supply the various works. At the same time, a central station was ing planned at Gröba to supply four districts of the kingdom of Saxony. Arrangements were accordingly to utilize, instead, the power generated at the Lauchhammer plant. Three turbo-dynamos of 5,000 kilowatts each are being installed, and two more units will be added later. The current is generated at 5,500 volts, and raised by means of transformers to the transmission tension of 110,000 volts. The plant will have a capacity of 40,000 kilowatts, or nearly 50,000

In order to light and heat the Office Building of the Senate and the Office Building of the House of Representatives, as well as the Capitol and Congres sional Library, a large power plant has been This is situated at Garfield Park by the government. The boiler room of the plant is provided with sixteen watertube beilers, each of 600 horse-power. construction of this plant, care has been taken to prevent any interruption of service. All the equipment is provided in duplicate. The generating equipment 2,000-kilowatt, three-phase turbo-gen putors, running at 1,500 revolutions per minute, and nerating a current at a pressure of 6,600 volts. I-cell storage battery plant may be used in case of emergency, to light the plant or the buildings.

In view of the efforts at the present time to curb amateur wireless telegraphers and the protest of the latter against monopoly of the atmosphere by commercial and government stations, it is interesting to note the decision recently handed down in the case of the Lake Shore and Michigan Southern Railroad pany, the Postal Telegraph-Cable Company, and the Western Union Telegraph Company versus the Chicago, Lake Shore and South Bend Railway Company Suit was brought against the latter company because its 6,600-volt single-phase trolley line affected inductively the lines of the telegraph companies and the system of the railroad company. held that the use of the single-phase alternating current on one's own premises does not constitute a nui sance, even though the electricity may escape and with the operation of electrical devices on adjoining property; that the companies bringing suit held no monopoly of the atmosphere, and if they found their systems interfered with, that they should provide such mechanical or electrical devices as would protect their lines.

With a view to standardizing methods of testing insulating materials, the American Society for Testing Materials has appointed a committee which will inves tigate the systems of the different manufacturers. The following is a list of the tests that are to be looked into, and, if possible, standardized: Electrical Tests: Dielectric strength (puncturing voltage); relative dispecific inductive capacity: electric hysteresis; direct current; (2) alternating current; conductivity insulation resistance; leakage. Physical Tests: Specific gravity and specific weight: hardness: tough ess; brittleness; ductility; workability; flexibility (with reference to varnished cloths, etc.); tensile, compressive, and shearing strength; fibrous, crystalline, and amorphous fracture; ability to take polish; melting point: oftening point; shrinkage; adhesiveness; effect of high temperature (electric arc); effect of low temperature (extra cold); artificial aging test; porosity; viscosity; flash and fire test; film-making power; rate of drying; penetration; absorption of moisture; amount of volagiven off at prescribed temperatures tile matter Chemical Tests: Proximate composition; solubility in water, oil stc.; effect of moisture and moist air; weathering qualities; chemical effect upon metals in contact; presence of acid.

AERONAUTICS.

There is a movement on foot in France to have the standards bearing high-tension electric cables painted a distinctive color. The danger is obvious enough, so that the suggestion seems worth carrying out.

Competing for the Coupe Femina, Mile. Marvingt, flying in an Antoinette monoplane, remained in the air 53 minutes, and covered a distance of 45 kilometers. The cup is offered to the woman who flies the greatest distance without stop up to December 31st.

In their annual reports, Major-General Leonard Wood and Brigadier-General James Allen recommend to Congress the appropriation of a sum of money for the purchase of aeroplanes. The art of aviation has assuredly reached such a stage that Congress ought no longer to deny these insistent requests.

In a lecture before the Institute of Civil Engineers of France, Prof. Soreau states that the Aero Club of France has issued over 270 licenses, and that the total number of aviators in the world is about 500. The deaths have been about six per cent. The total distance flown may be estimated at 125,000 miles.

The Aero Club of France has decided to uphold the Royal Aero Club in its protest, instigated by Grahame-White, over the British aviator not being allowed another trial in the Statue of Liberty \$10,000 prize race at the Belmont Park meet. It will probably take a year before the matter is definitely settled by the International Aeronautic Federation.

Major Kennedy, at a recent meeting of the Royal Societies Club, discoursed on aeroplane accidents. He classified the causes of forty British accidents at Doncaster, Bournemouth, and Lanark, as follows: Failure of engine and involuntary descent, 13; alighting on bad ground, 10; struck by sudden gust of wind, 6; fire and similar causes, 6; propeller breaking, 5.

The British War Office has decided that Salisbury Plain shall be the flying ground for the British army aeroplane corps. The plain is even now the scene of much aeroplane activity. There army men may be seen in flight almost every day. The type of machine has not yet been decided on. A Paulhan biplane, a Farman biplane, and a two-seated Blériot have been ordered from France. English machines will also be tested.

When the Wright suit against Grahame-White for the use of his Farman biplane comes to trial, M. Henry Farman will probably produce several heretofore unknown foreign patents which he has purchased and which, he claims, clearly anticipate those of the Wright brothers. At the same time the Farman brothers—for Maurice and Henry Farman are now working together—are threatening to prosecute all infringers of the several patents which they hold in common.

After terminating his flying in America with a tenday exhibition at Philadelphia, Grahame-White returned to England on the 30th ultimo, carrying with him the International Trophy he won at Belmont Park. His earnings during his three months' visit are said to be about \$100,000 in cash. The Wrights have sued White for infringement of their patents, and he expects to return in a month to defend the suit. Before leaving, he ordered seven biplanes from the Burgess Company and Curtiss. This is the largest single order yet given in the United States.

It has not yet been definitely determined whether or not Mr. J. Armstrong Drexel broke the late Ralph Johnstone's height record of 9,714 feet. Before making his attempt, Mr. Drexel had his Richard barograph tested by Queen & Co., of Philadelphia, who make a similar instrument. The barograph was verified up to a height of but 9,600 feet, however. During the past week the National Council of the Aero Club of America had the barograph tested by Messrs. Snyder & Co. of New York, who claimed that Mr. Drexel had only reached a height of 9,450 feet instead of 9,970, as at first reported. The instrument has been returned to Queen & Co. for a final test, which will be made under the supervision of officers of the Weather Bureau. In case it is found that Johnstone's record was not beaten, Mr. Drexel intends to make a new trial.

It seems that Augustus Post and Allan R. Hawley did not break the world's record for long-distance ballooning, after all. An official report made by the War Department shows that Comte de la Vaulx's distance of 1,193 miles, made in a flight from Paris to a point in Russia, has not been beaten. The official record made by the "America II." was 1,171.13 miles. The records made by the other entrants are as follows: The "Düsseldorf II.," pilot Gericke, 1,131 miles; "Germania," pilot Capt. von Abercron, 1,079 miles; "Hamburg III.," pilot Col. Schaeck, 826 miles; "Hamburg III.," pilot Lieut. Vogt, 766 miles; "Azurea," pilot Capt. Messner, 756 miles; "Isle de France," pilot Alfred Leblauc, 722 miles; "St. Louis IV.," pilot H. E. Honeywell, 552 miles; "Condor," pilot Jacques Faure, 413 mile; "Million Population Club," pilot Von Phul, 317 miles.

SCIENCE.

The prize of £20 offered by the Scottish Meteorological Society for competition among students and graduates of the Scottish universities for the best essay on a meteorological subject has been awarded to David MacOwan, of Edinburgh University, for an essay on "Observations in Atmospheric Electricity in and near Edinburgh."

From a recent report of the Japanese Resident General in Korea it appears that the official meteorological work of that country has been transferred to the Agricultural Bureau, and that forty-five meteorological stations were in operation in 1908, while storm signals were displayed at eleven seaports. The central observatory is at Chemulpo.

In its last annual report the British Meteorological Office announces that it has in preparation the following special publications among others: "The Computer's Handbook," "The Seaman's Handbook," "Gales on the British Coasts" (a revised edition of the "Fishery Barometer Manual"), "The Seasons in the British Isles," "Atlas of Tropical Hurricanes."

The Japanese Antarctic expedition, under Lieut. Shirase, started on Monday, November 28th, from Shinagawa Bay aboard the 450-ton schooner "Kainan Maru." It is admitted that the Japanese equipment is so poor that it is not likely that the expedition can accomplish much. The crew of the schooner consists of fifteen picked men. Manchurian ponies will be employed, following the example of Shackelton.

Prof. Roy C. Andrews, of the American Museum of Natural History, has returned to New York, and has brought with him some very remarkable specimens from Asiatic waters. One of them is a new species of porpoise, captured off the coast of Japan, another a new variety of whale, likewise caught not far from the Japanese coast. The new whale, which Prof. Andrews christened the "Sardine Whale," grows to a length of about fifty feet, is more slender than the humpback or sperm whale, and commercially is of less value.

No star has yet been found with a parallax as much as one second of arc, and it is practically certain that there exists none near enough to have that amount of parallax. In the southern hemisphere there is a bright star, known as Alpha Centauri, with a parallax of three-quarters of a second. The distance of this nearest of all stars is about 26 millions of millions of miles—nearly three million times as far from us as the sun, a distance from which light would take four and one-quarter years to reach us. Something is known now of the parallax of some 360 stars, but in many of these cases the result is exceedingly uncertain.

Sir W. Crookes states that scandium has been found to the extent of more than one per cent in the mineral wilkite from Finland, and in small amounts for many other minerals. By a systematic series of fractionations it is possible to separate scandium from most associated elements; ytterbium is the most difficult to separate because its nitrate is decomposed almost as readily as scandium nitrate. In view of the atomic weight relationships, and of the frequency with which these elements occur together in nature, it is suggested that yttrium and scandium are degradation products of ytterbium. Scandium can be separated from yttrium and ytterbium by precipitation as metanitrobenzoate.

For producing perfect asepsis of wounds and of areas that have to be prepared for surgical operations, especially where a thorough scrubbing would involve considerable pain, tincture of iodine of official strength has proved itself entirely satisfactory in a large number of cases, and its application for this purpose is rapidly extending, particularly in Germany. The tincture is applied by means of a brush, in thin layers, without previous cleansing of the wound or surface, except that sometimes benzine and alcohol are used to remove excess of grease. Inflammation from the iodine is very rare, and this danger is more than compensated by the advantages of the method.

By means of experiments carried on during the past summer at the Biological Laboratory of the U. S. Bureau of Fisheries, at Woods Hole, Mass., G. Q. Scott, of the College of the City of New York, and G. F. White, of Richmond (Va.) College, have determined that the gills of fishes are permeable to salts The experiments consisted in making chemical analyes of the blood drawn from a salt-water fish that had been placed in fresh water, the blood being sampled at intervals of from thirty to forty-five minutes. Not only does the blood of the fish become diluted through absorption of fresh water through the gills, there is an actual loss of salts from the body. results are in harmony with those obtained by Dr. F. B. Sumner, director of the government laboratory at Woods Hole, five years ago, and explain, in part, the death of salt-water fish placed in fresh water, and vice versa.

AN ENGLISH AUTOMOBILE TURBINE FIRE PUMP

BY FRANK C. PERKINS

A century ago the best fire brigades were provided with manual fire engines, although the usual fire fighting appliances consisted of a hand squirt and a number of buckets. Later, a combined pedal and hand pumping machine was devised, and fortunate indeed was the fire brigade owning one of these equipments, the steam 're engine being then unknown. Somewhat

over six decades ago the first steam fire engine was built. It was self-propelled, and the engine served the dual purpose of propelling and pumping. It was not a success however, as the weight was too great and the cost of construction and maintenance was such that the self-propulsive idea was abandoned.

The horse-drawn steam fire engine was evolved from the last named apparatus, and has probably reached at the present date the highest degree of perfection which its form of construction permits. The one thing that it lacks is speed, which can be given to it only through the abandoned steam-propelling system.

doned steam-propelling system.


It is well known that the steam motor fire engine now in use is almost as heavy as the first one constructed, and is not only costly to run, but is a continual expense day and night, as steam must be kept up when in the station.

The gasoline engine or internal combustion motor has solved the diffi-

culty of the motor steam fire pumps, as it is as well suited for pumping as for propelling. While steam engines require furnaces and boilers, and electric motors require accumulators or storage batteries, the gasoline motors need nothing but a small carbureter and a fuel tank. Besides they are self-contained and can be started up with a single turn of the starting handle. The motor fire pump is infinitely superior in point of speed and first cost as well as economy in operation, and they combine quietness and long life with their other good points.

The Leeds auto fire engine shown in the accompanying illustration has a capacity of 350 gallons, and is operated by a four-cylinder engine of \$5 brake horse-power. This auto fire car has four speeds forward

and one reverse, with a normal speed of 35 miles per hour under load. It will deliver 350 gallons of water at 120 pounds pressure, throwing a 1½-inch jet 160 feet high. The turbine-pump is self-charging and automatic in its action. The car is equipped with block section tires and provided with a 45-foot fire-escape ladder. Seven similar auto fire engines are



AUTOMOBILE TURBINE FIRE PUMP IN USE AT LEEDS AND OTHER ENGLISH CITIES.

operated by the London Fire Brigade, and others of this type are in the fire service of several English cities,

The pump, of the centrifugal rotary or turbine type, has a single casing designed to do exactly the same work as those usually requiring three or more casings. By this means the weight is reduced to less than half and the efficiency increased. It has, too, the important feature, that the incoming water enters equally on both sides and obviates end thrust, which is a serious defect in other makes of pumps of this type. The pump is self-charging, so all that is required is to drop the suction hose in the water and to start the engine, when instantly the pump is in full operation. A very special advantage about this pump for fire

purposes is, that presuming at the side of the fire there is a water main carrying pressure, such a main can be connected directly to the suction of the pump and the pump will add to such pressure. This is an important feature, as the pressure in the mains is wasted by letting the water out into a suction tank and then drawing it up again, or by the obstruction offered

by the operation of the valves if the hydrants be direct coupled to the suction head.

In the Leeds auto fire engine the transmission system from the engine to the pump is exceedingly simple, as geared to the clutch shaft driving the road wheel gears is another shaft which has no connection whatever with the road gears. Normally, the pump shaft is not in gear with the clutch shaft, but as soon as the vehicle stops at a fire a small lever is pulled over and the pump shaft is thrown into gear with the clutch shaft, which is still being driven from the engine. The road gears are in the "neutral" position when the pump is at work.

It is maintained that it is impossible to burst the delivery hose by shutting off the water while the pump is running, as would happen with ordinary thrust or piston pumps. All that would happen would be the running of the vane vessel through the pump chamber rast the water inclosed therein. The delivery hose is controlled by separate

therein. The delivery hose is controlled by separate regulator valves; consequently, shut-off nozzles may be used and unnecessary water damage prevented.

In English fire departments the charging apparatus of the fire pumps is used as a first-aid machine when the main pump supply is not required. By starting the pump, a continuous supply of water from a 50-gallon charging tank is delivered through a 1-inch hose with 5/16-inch nozzle, the supply being maintained by coupling a hydrant to the tank. The engine drives the pump and maintains the requisite pressure. The main line of 2½-inch or 2%-inch hose can be brought into play at any time, while the 1-inch first-aid hose is at work should the fire assume serious proportions.

A NOVEL ERGOGRAPH

BY DR. ALFRED GRADENWITZ


One of the most important factors in connection with psychological research work is the variable strength of a given muscle. In order to ascertain this, a number of apparatus termed ergographs have been constructed, the most well-known of which is the

Mosso apparatus. As, however, none of the arrangements so far designed actually complies with such conditions as are entailed by the very nature of muscular work, Prof. J. Athanasiu of Bucharest University has constructed on quite novel principles the ergograph represented in the accompanying illustration.

The weight to be lifted, which serves to determine the muscular effort, is a perfectly spherical massive steel ball sliding on the two aluminium plates seen on the bench placed against the left end of the experimental table. The two plates are hinged round a horizontal axis, their edges being bent conveniently so as to prevent the ball from falling to the floor.

The subject to be experimented on is seated at the experimental table, his arms being strung to two wooden planks which are likewise hinged round a horizental axis. Non-extensible strings connect each of the planks with one of the aluminium plates so that by pushing down either of the planks, the corresponding aluminium plate, and along with it the steel hall, is lifted more or less according to the strength of the subject.

The plate thus lifted forms an inclined plane along which the ball will roll down toward the other side, a wall lined with a flannel cushion serving to damp the impact. As the ball during the time the aluminium plate is lifted should remain at the free end of the latter, a convenient arrangement consisting of five longitudinal slots fitting into a series of wooden bars



A SUBJECT UNDER A TEST OF MUSCULAR STRLINGTH IN POSITION AT A

has been provided to prevent the bail from recoiling.

The lifting curve which represents the muscular effort of the subject is recorded by an electrically operated signaling style, consisting of a straw, pivoting upon a horizontal axis, and which at its end carries

a soft iron armature acted upon by an electromagnet. The electric circuit contains the aluminium plates and three thin transversal wires.

The ball rolling up and down in its aluminium trough produces two current closures which are recorded by the style above described. The lifting curve thus comprises two interruptions corresponding to the beginning of the ball motion and to the passage of the ball from one plate to the other respectively.

A special feature of this double ergograph is, that the weight to be lifted will decrease as the contraction of the muscle proceeds, in order finally to become nil. As the weight, after the muscular contraction has been completed, loses any connection with the muscle, the latter only performs positive work, returning quite freely into its position of rest. Again, the new apparatus allows permanent work to be readily performed. It enables two muscles of the same or different persons to be checked with one another and would seem to be especially adapted for use in gymnasiums where records of the muscular development of athletes under differen: methods of training could be made and from these the value of the different muscle-developing apparatus determined.

FLYING MACHINES, LIVING AND LIFELESS

WHAT MAN HAS LEARNED FROM NATURE


The art of flying must be learned from birds and other flying creatures, and the study of their anatomy has contributed much to the development of the aero-

The great schools of aviation are the ponds covered with dragon-flies, the fields gay with fluttering butterflies, and the lofty cliffs whence the great soaring birds of the sea take their flight. From birds and insects man has learned how to leave the earth, to rise, advance and change his course, and to land with safety, and the sustaining surfaces of the aeroplane are imitations of living wings.

The structure of a bird's wing is not generally under-stood, because it is usually concealed by rapid movement or by the folding of the wing when at rest. In soaring flight, the wing assumes a comparatively simple form, slight-

ly convex above and concave below. The wing of a corresponds to the arm and hand of a man, but the homologous parts do not have the same rela-

sions in the skeletons o f the two members. The forearm of the bird is longer than the upper



butterfly's ability to fly.

arm, and the

hand has only

two very long fingers and a rudimentary thumb. The wings of many insects are comparatively

simple and invariable in form,

A dragon fly which has just; emerged from its pupa skin (shown behind the insect).

consisting of a frame of horn-like fibers covered with a thin and usually transparent membrane.

A wonderful spectacle is presented by the sudden apparition of an insect's wing at the completion of its metamorphosis. The transformation of the grub into the butterfly, though familiar, is none the less amazing, but the evolution of the active and gossamerwinged dragon-fly, from its ugly and sluggish aquatic pupa, is still more impressive. Early on a May morning the pupa emerges from its cocoon at the bottom of a ditch, swims on its back, by paddling with its long-haired paws, to the stem of an aquatic plant, and climbs up out of the water. Then, after a

momentary pause, the skin suddenly bursts open and the perfect insect appears, with closely folded wings, which soon unfold and assume their form. The older naturalists thought that the insect "swallowed air," with which the wings were inflated. In reality the air is absorbed in the digestive organs, causing an increased blood pressure which mechanically expands the wings. The presence of dew is also necessary, hence the first flight is always made at dawn. This spectacle of the birth of a wing may be observed in dragon-flies reared in an aquarium, the atmosphere of which should be moistened with an atomizer when the pupa rises to the surface.

Man, like the dragon-fly, now appears to be emerging from his humble larval existence and expanding his wings in flight.

The most successful fliers, among birds and insects, pass before our eyes

so swiftly that we cannot observe the mechanism by which they are sustained and carried onward. The secret of flight can best be learned from a bird which

One of nature's biplanes in

flies slowly and heavily. A hen, in attempting to fly, runs rapidly over the ground, leaps high into the air, and beats her wings furiously, with an effort that

The long and slender form of soaring

birds facilitates their flight.


often elicits cries of pain. These actions ex-plain themselves. The hen runs because a great horizontal velocity makes it easier to rise, and her wings are so small that they must flapped violently in order to take sufficient hold on the air. Eagles, vultures, and other large-winged birds do not need to move their wings so energetically, but they, too, are compelled to leap upward in order to rise from a level plain.

A bird's wing, in its downward stroke, presses and rests upon the air beneath. Why is not the upward impulse thus produced followed by an equal downward impulse when the wing is raised? On the down stroke the free edge of each feather is held down by the strong quill of the next, which lies over it and against which it is pressed by the air, so that the whole wing forms a continuous resisting

surface. On the up stroke, on the contrary, the free edge of each feather, being unsupported beneath, is bent downward by the air pressure above, leaving an interstice between it and the next feather, so



Marey's experiment, showing helical movement of an



A monoplane compared with a soaring bird. FLYING MACHINES, LIVING AND LIFELESS.

that the wing moves upward through the air with comparative freedom. These movements of the feathers are shown clearly by Marey's instantaneous

photographs. Nothing similar to this is possible with an insect's wing, which is made of one piece, but the mechanism of the flight of insects was also revealed b the instantaneous photographs and experiments of Marey and Pettigrew. Although these two investigators engaged in lively controversies and their theories differ in de tail, both demonstrated, almost at the same time, that the tip of an insect's wing describes a figure 8 and that the plane of the wing changes, so that the wing, as nearly as the continuity of living tissues permits, opposes its entire surface to the air on the down stroke and cleaves the air with its edge on the up stroke. Marey deter-

mined this helical movement by holding a glass rod, blackened in a flame, against the wing of an insect struggling to escape.



Skeleton of a bustard, showing rudimentary thumb and relative lengths of wing bones,

The great soaring birds, which make the longest and loftlest flights, flap their wings very little. The flight of a soaring bird is a succession of glides down almost imperceptibly inclined planes. Drzewiecki has calculated that if a soaring bird, starting from an elevation of 3,300 feet, falls with its wings held rigidly at the most favorable inclination to the horizon, it will strike the ground at a point more than 14 miles distant from its starting point. Hence an eagle, swooping from its mountain eyrle, may soar completely across the field of view without flapping its wings

and without descending perceptibly.
When a sea breeze blows against the face of a lofty cliff it is deflected upward. Under these conditions a bird starting from the top of the cliff may actually rise to a much greater height without flapping its wings. In extended flights in still air, the course of a soaring bird is zigzag, or undulating, in a vertical plane. Long and very slightly inclined downward glides, accomplished by soaring alone, alternate with steep and short ascents, effected by a few strokes of the wings. In a perfectly steady and uniform wind the path is the same, relatively to the moving air, while the bird's motion, relatively to the ground be-neath, is the resultant of its motion, relatively to the air, and the motion of the air itself. It is often asserted to-day, as it was asserted by Leonardo da Vinci in the fifteenth century, that (Concluded on page 468.)

RULES GOVERNING THE COMPETITION FOR THE \$15,000 FLYING MACHINE PRIZE OFFERED BY MR. EDWIN GOULD.

 A prize of \$15,000 has been offered by Mr. Edwin Gould for the most perfect and practicable heavierthan-air flying machine, designed and demonstrated in this country, and equipped with two or more complete power plants (separate motors and propellers), so connected that any power plant may be operated independently, or that they may be used together.

CONDITIONS OF ENTRY.

2. Competitors for the prize must file with the Contest Committee complete drawings and specifications of their machines, in which the arrangement of the engines and propellers is clearly shown, with the mechanism for throwing into or out of gear one or all of the engines and propellers. Such entry should be addressed to the Contest Committee of the Gould Scientific American Prize, 361 Broadway, New York city. Each contestant, in formally entering his machine, must specify its type (monoplane, biplane, helicopter, etc.), give its principal dimensions, the number and sizes of its motors and propellers, its horse-power, fuel-carrying capacity, and the nature of its steering and controlling devices.

3. Entries must be received at the office of the SCIENTIFIE AMERICAN on or before June 1st, 1911. Contests will take place July 4th, 1911, and following days. At least two machines must be entered in the contest or the prize will not be awarded.

CONTEST COMMITTEE.

4. The committee will consist of a representative of the Scientific American, a representative of the Aero Club of America, and the representative of some technical institute. This committee shall pass upon the practicability and efficiency of all the machines entered in competition, and they shall also act as judges in determining which machine has made the best flights and complied with the tests upon which the winning of the prize is conditional. The decision of this committee shall be final.

CONDITIONS OF THE TEST.

5. Before making a flight each contestant or his agent must prove to the satisfaction of the Contest Committee that he is able to drive each engine and propeller independently of the other or others, and that he is able to couple up all engines and propellers and drive them in unison. No machine will be allowed to compete unless it can fulfill these requirements to the satisfaction of the Contest Committee. The prize shall not be awarded unless the competitor can demonstrate that he is able to drive his machine in a continuous flight, over a designated course; and for a period of at least one hour he must run with one of his power plants disconnected; also he must drive his engines during said flight alternately and together. Recording tachometers attached to the motors can probably be used to prove such performance.

In the judging of the performances of the various machines, the questions of stability, ease of control, and safety will also be taken into consideration by the judges. The machine best fulfilling these conditions shall be awarded the prize.

6. All heavier-than-air machines of any type whatever—aeroplanes, helicopters, ornithopters, etc.—shall be entitled to compete for the prize, but all machines carrying a balloor or gas-containing envelope for purposes of support are excluded from the competition.

7. The flights will be made under reasonable conditions of weather. The judges will, at their discretion, order the flights to begin at any time they may see fit, provided they consider the weather conditions sufficiently favorable.

No entry fee will be charged, but the contestant must pay for the transportation of his machine to and from the field of trial.

 The place of holding the trial shall be determined by the Contest Committee, and the location of such place of trial shall be announced on or about June 1st, 1911.

The provision of a quick stoppage is an advantage hitherto restricted to direct-current motors, which can act as generators; with alternating induction motors the braking must be produced by external means. A suggestion of Mr. A. Héreng is given in L'Industrie Electrique for removing this drawback, by providing a suitable excitation for the stator of an induction motor during the act of stopping, which enables the rotor to generate alternating currents and thus to absorb energy. The desired end may be attained by coupling a small series direct-current machine to the motor, connected so that when the main circuit is opened, the direct-current machine is coupled to one of the stator phases and excites the field, while the rotor is either short-circuited or connected to a resistance. Alternately a rectified current derived from one of the rotor

phases—in the case of a wound rotor with slip rings may be used to excite the stator field, the current being rectified either by an electrolytic valve, a commutator, or other means.

SOME INCIDENTS IN THE EARLY LIFE OF FERRANTI.

BY A, J. JABMAN.
Sebastiani Ziani de Ferranti, the newly-elected president of the British Institute of Electrical Engineers, is the son of Casar Ferranti, an eminent photographer of Bold Street, Liverpool, England. It at St. Augustine's College, Ramsgate, Kent, that Mr. Ferranti, who was being educated there, met with accident that nearly caused the loss of his eyesight, while fitting up an electric bell between the college and the monastery. One of his battery carbons was broken, and he endeavored to join the two ends gether and fasten them with a lead bond. The carbon pieces were suitably drilled and molted lead was poured into the hole; but the young experimenter had neglected to dry the carbon thoroughly, and as a consequence, there was an explosion due to the instant conversion of the moisture into steam. was thrown into his face, blinding him for a time, and burning him badly. This was in 1879.

The first dynamo Ferranti ever saw was at 41 Queen Street, Ramsgate. It was driven by hand power, and was fitted with shuttle-wound H-pattern Slemens armature. In 1881 Mr. Ferranti became located in London. It was at No. 10 Glenarm Road, Lower Clapton, that Mr. Ferranti commenced the design of a new alternating current dynamo. His idea was to convert Faraday's disk into a practical armature. Here Mr. Ferranti and the writer often conversed upon the subject, and during his stay at this address the photograph herewith published was made. It was taken at night by the light of an arc lamp, with an exposure of four seconds. The current was furnished by a 44-cell bichromate battery, and the arc



FERRANTI IN 1881. PHOTOGRAPHED BY THE LIGHT OF AN ARC LAMP OF HIS OWN CONSTRUCTION.

was fitted with a 6-millimeter positive carbon and a plece of quarter-inch copper wire for the negative pole. This was probably the earliest use of a copper pole in an arc lamp.

In 1882, Ferranti had completed the design of a new alternating current machine, and had protected his invention with a patent. The machine was made writer's electrical workshop, then at 25 Richmond Street, St. Luke's, London, The machine was tested here, the magnets being excited by a current of 16 amperes at 65 volts from a shunt-wound dynamo. It lighted 42 16-candle-power incandescent lamps on a parallel circuit, the available power being insufficient to produce the best effect. It was here that Sir William Thomson (late Lord Kelvin) saw this machine The design of the mawork lighting the lamps. chine was similar to that of his own "mouse mill" ma-The dynamo weighed half a ton. The armature copper strip was insulated with black cotton tape made and fitted by the writer. It was eventually presented to the Museum of Patents at South Kensington. The making of the cotton strip armatures and magnet coils was carried on in the writer's workshops for several months, and eventually these alternating current generators were manufactured at the Appold works Ferranti, Thomson, and Ince.

Ferranti's 10,000-horse-power alternating generator was fitted at Deptford. Much to his surprise, it was found that the electro-motive force was much higher at the end of the line than at the generator. This was due to the fact that the concentric conductor acted like a Leyden jar. This came to be known as the Ferranti effect. The difficulty was eventually overcome. It entailed a loss of 16 amperes at 10,000 volts in a 6-mile conductor, due to static charge.

In Mr. Ferranti the Institute of Electrical Engineers has chosen a man of high electrical skill and mechanical qualifications, having gone through the mill of practical experience. His alternating current

meter, as well as the current generator, will stand as monuments to his skill and ability.

[Note,—Mr. Ferranti's presidential address before the Institute of Electrical Engineers was unusually interesting. It is republished in full in the current SCIENTIFIC AMERICAN SUPPLEMENT.—Ed.]

OIL LOSSES BY FIRE.

BY CHARLES A, SIDMAN

It has been estimated by the Geological Survey of the Department of the Interior that there is lost annually more than a million and a half barrels of oil by the burning of oil wells, and from other causes.

The greatest loss is during the months of May to October, and is occasioned by any number of causes. The principal one seems to be the careless use of matches. Other reasons which cause fires in oil wells are from lightning, from the spark of an automobile, and from the gases which emanate from the wells.

It sometimes happens also that a well is flowing at such a great rate that the bearing of the pump may develop a serious leak, and spray a great many barrels of oil on the ground before it can be stopped. If a thunder storm should arise at that time, there is danger of the well's catching fire from lightning, and causing a great deal of damage as well as loss of life.

A case of this kind happened this past spring in the State of Louisiana, with a very large well which had a flow of oil variously estimated at from 8,000 to 25,000 barrels a day. A leak developed which could not be stopped at once, and while waiting for suitable machinery to arrive, a severe thunder storm broke out. The well had been spraying oil from the leak for several days, drenching the men working near it, which made it especially dangerous for them, for it happened that the oil was of such a gravity that it contained about twenty per cent of gasoline and was very inflammable.

The men who were working on the well are termed "greasy men," and when this storm came up were ordered to a nearby stream of water, so that if lightning did strike the well they could plunge in and thereby save themselves.

The well was struck, and there immediately began a fight to extinguish the fire. The gases in the well threw the oil to a great height, causing danger to life and property as well.

The simplest method to extinguish the fire seemed to be to drown it out by means of steam. Twenty-five steam boilers were secured from a nearby city, brought to the well, and attachments made with a nearby natural gas well, and the fire was extinguished within forty-eight hours. For several hours afterward the ground was sprayed with hot steam to be sure that no fire remained.

There are several ways of effectively stopping a fire in an oil well. It can be stopped by water to a certain extent, but the danger of the oil's spreading, and of the vapor thrown off by the evaporation of the water does not make it safe to try this method with a large fire. In cases of small fires it might answer, but not always. Steam driven by force pumps is an effectual means of killing a fire, and is resorted to in most cases. In many of the oil fields one will see many buckets of sand lying around the wells. Aside from being a cheap method of fighting fire, it is also one which can be performed with ease, for a man can pick up a bucket and stop an incipient fire almost as soon as it has started.

Many of the large and modern oil companies have had installed in their fields and near their refineries a system of high-pressure water pipes for use in such cases of sudden fires. High-pressure steam pipes are also run into the fields for the same purpo interesting to note in the case of a field of tanks, the means taken to prevent fires. The majority of the tanks have a sort of sprinkler system installed. large iron pipe is placed around the top of the tank. This is punched full of holes, and at the outbreak of a high pressure is turned on, which causes a flow of water to run down the outside of the tank. At the same time hot steam is introduced inside of the tanks by the same means as the water is, which prevents the gases or vapor inside of the tank from If the tank does begin to burn from catching fire. the top, then the oil is pumped from the bottom of the tank into another one, thereby saving a great deal

One of the principal and most important positions with any oil company is that of fire marshal. It is his duty to know the position of all the fire plugs, just what connections are to be made, and to take complete charge in cases of fire. Upon this "emergency man" depends the saving and salvation of the oil men.

There are discovered from time to time what are known as freak wells. One in particular is located in Mexico. It was drilled with every indication of producing a big supply of oil. After the nitro had been set off there gushed forth a volume of hot water, mud, stones, and very little oil. The gases in the oil and the force of the explosion caused the opening, which

was sixteen inches at the start, to widen out so much that this time it spread over an area of more than forty acres. At the time it spouted, the woods around it caught fire, and many thousands of dollars was spent in putting it out. At this time very little oil is taken from the well, and its spoutings are inter-

There are many erroneous ideas as to the handling of kerosene and gasoline. It is not generally known that oil, that is, kerosene, is not explosive. A simple experiment can be tried to demonstrate this fact. Place a small saucer of kerosene on a table, and throw a lighted match into it. In every case the oil will put out the light from the match. Gasoline also is not explosive. It is the vapor thrown off from the gasoline that causes the explosion. In the case of kerosene, the flame is put out because the oil is cold and there is no vapor. But hold a match to a wick which feeds on oil and you can light the wick. That is because there are but few drops of oil on the wick, which draws more oil when that is exhausted.

The petroleum market has advanced to such an extent, that all modern locomotion is now by gasoline The auto and aero also use gasoline, and or oil. where formerly the auto used steam, now the only article is gasoline.

The Current Supplement.

There are few subjects more important to the people of this country than the question of the ever-growing rate at which we use up our coal supplies. to effect true economy in the use of our natural fuel resources was the subject of a brilliant paper by Mr. Z. de Ferranti before the Institute of Electrical He outlined a plan for converting the Engineers. whole of the coal which we use for heat and power into electricity and the recovering of its by-products at a comparatively small number of great electricity-Mr. Ferranti's paper attracted producing stations. much attention in England. In the current issue of the Supplement, No. 1823, will be found his paper and also a critique of his views, republished from a well-known English journal.—This being the holiday season, readers of the Supplement will no doubt peruse with interest an article on "Up-to-date Toys."—Mr. Barnet describes the motor lifeboats of the Royal National Lifeboat Institution.-The first Norwegian electric steel works is described, in which the Hiorth system is adopted.-In the year 1896 the Dutch physiman discovered that the two yellow lines into light of a Bunsen flame colored by sodium is resolved by the spectroscope, become broader when the flame is placed between the poles of a powerful electro-magnet, and resumed their normal width when the current which energized the magnet was turned The current Supplement gives an excellent simple analysis of this so-called Zeeman effect, an analysis which ought to explain to every man who has no technical education just what the Zeeman effect is, and what causes it.—Mr. Lindon Bates, Jr., writes on "The Briquetting of Coal in Belgium."-Mr. Arthur R. Colburn presents the second installment of his new soluof the famous Pons Asinorum problem in geometry.

Official Meteorological Summary, New York, N. Y., November, 1910.

Atmospheric pressure: Highest, 30.37; lowest, 29.49; mean, 29.81. Temperature: Highest, 65; date, 2nd; lowest, 29; date, 20th; mean of warmest day, 58; date, 2nd; coolest day, 35; date, 20th; mean of maximum for the month, 46.7; mean of minimum, 36.4; absolute mean, 41.6; normal, 44.0; average daily deficiency compared with the mean of 40 years, 2.4. Warmest mean, 50, in 1902. Coldest 37, in 1873, Max. and min. for November for 40 years, 74 and 7. Average daily excess since January 1st, 2.1. Precipitation: 4.62; greatest in 24 hours, 3.16; date, 3rd and 4th. Average for November for 40 years, 3.44. Accumulated deficiency since January 1st, 7.15. Greatest precipita-tion, 9.82, in 1889; least, 0.75, in 1908. Wind: Prevailing direction, west; total movement, 10,506 miles; average hourly velocity, 14.6 miles; maximum velocity, 46 miles an hour. Weather: clear days, 2; partly cloudy, 14; cloudy, 14; on which 0.01 inch or more of precipitation occurred, 8. Relative humidity, mean of 8 A. M. and 8 P. M., 68.6. Heat and moisture summary of the autumn: Average temperature, 56.03; al, 55.37. Average precipitation, 3.35; normal, Average humidity, mean of 8 A. M. and 8 P. M., normal, 55.37.

Of fifteen adjudicated patents reported in the Patent Office Official Gazette of November 8th, 1910, it is noted that seven patents were held to be valid and infringed, four patents were held valid and not infringed, and one patent was held void as a mere aggregation of old parts, two patents were held void for anticipation, and one patent was held void for lack of patentable novelty. Elever patents, it will be noticed, were held valid. Correspondence.

Scientific American

OLD BALLOON VOYAGES TO CANADA.

To the Editor of the SCIENTIFIC AMERICAN:

In connection with the letter of O. H. Ingram, Eau Claire, Wis., published in your issue dated November 419, the following may be of interest:

About 1854 one La Fountaine and another whose name I never knew, or have forgotten, started in balloon from St. Louis, Mo., and floated northeasterly over Illinois, Indiana, the whole length of Lake Eric and Lake Ontario, landing, the day after starting, on the shore of Lake Ontario, a little south of Sackett's Harbor. According to the description of this trip in the newspapers of that time, this balloon continued at a comparatively low altitude, estimated at about 400 or 500 feet above Lake Erie, and falling lower over Ontario, falling so low at the last that all ballast and outer garments of the sailors were thrown and before reaching the shore the men climbed into the rigging and cut away the basket, and even then for the last few miles, they would touch water and again, such jumps growing shorter until at last they were dragged ashore wet and nearly naked. The balloon landed on the sandy beach, and stopped without serious damage in low trees on the of the lake

A few days later, the same parties made an ascent from Watertown, N. Y., the afternoon of July 4th, as I now recall, a great crowd being present to witness I was living with my parents at Diamond Lake, Lake County, this State, and father and mother were visiting relatives in Oswego County, New York, and Watertown, near which my grandmother was living. They saw this exhibit at Watertown, and mother gave a description of the same. The balloon sailed away to the northeast, and was not heard of for many days. La Fountaine and his companion were found by lumbermen after they had traveled two three days, and then with help returned, found the balloon, which had been damaged and I believe cut and in part taken away, supposedly by Indians, but much of it was rescued and taken back to civilization.

Such is the history as told by my parents and the papers of that time, as they rest in my memory. To my sons and friends I have narrated these events from time to time, as the subject of ballooning has come up for discussion, and they are substantially correct R. J. BENNETT.

Ravenswood, Chicago, Ill.

To the Editor of the SCIENTIFIC AMERICAN:

In replying to the letter of Mr. O. H. Ingram, re cently published in the Scientific American, in reference to the remains of a balloon found many years ago in the wilds of Canada, north of Ottawa, I can say that they were the remains of one of the most famous balloons and the result of one of the longest and most remarkable balloon voyages ever made. In August 1859, Prof. Wise, the celebrated aeronaut, and John La Mountain made their memorable voyage of over 1,000 miles, from St. Louis, and landed on the eastern shore of Lake Ontario, in Jefferson County, New York. I was then a boy, living in Theresa, in that county and remember the circumstances well and the still more tragic event that followed. Mr. John A. Haddock, of our town, a man of adventurous and enterprising disposition, induced Prof. La Mountain to take him up in the wonderful balloon. They ascended from Watertown one fine afternoon, September 22nd, 1859, and disappeared as if swallowed up in the clouds. Nothing was seen or heard from them for twelve days when a telegram announced their arrival at Ottawa in After traveling all night, they had landed the next day in an unknown wilderness, 180 miles north of Ottawa, in entire ignorance of their location or the distance they had traveled. They then wandered six days with incredible hardship, going four days without a mouthful of food. On the verge of starva tion, they were rescued by lumbermen, as described by Mr. Ingram. The full story is in Haddock's "History of Jefferson County, New York." BYRON A. BROOKS.

New York, N. Y.

A new feature in Shawia is, says the British consul at Casablanca, Morocco, the notable growth in the number of large foreign-owned farms. On some of these farms up-to-date agricultural machinery and implements are in use. Light iron plows, disk plows, cultivators, reapers, and traction engines (for road or plow), also wagons (of German make) have een seen on the quays at Casablanca. These goods are mostly of American, French, or British make. It is probable that the number of farms owned by foreigners in Shawia will continue to increase. With the gradual progress of Morocco, new commercial opportunities will arise and further districts will be or to trade. The natives of Morocco are very well disposed toward British traders and British goods.

The Future of Rubber in the Far East, BY CHARLES S. BRADDOCK, JB., PH.G., M.D., LATE CHIEF MEDICAL INSPECTOR ROYAL SIAMESE GOVERNMENT.

Advices from the Far East from Colombo, Penang, and Singapore say that the speculating public there as well as in London has gone mad rubber boom of 1910, on account of the high price of This boom will break as surely rude rubber. did the South Sea bubble of an earlier century. However, in the future the price of crude rubber will no doubt be lowered to a normal basis, and in a few years will be lower in price than it has many years, or may be to a still lower level. supply of the world, no matter how much may be the increase of demand, will be supplied almost cultivated plantations and jungles either of Brazil, Africa, or Indo-China. pendulum of time will swing so that the ruined coffee planters of Java, Sumatra, and the Malay Peninsula eturn the compliment by ruining the rubber industry of Brazil, as Brazil ruined them in the coffee busis, thus evening up matters in the eternal justice of things.

Up to within a few years a great proportion of the coffee crop of the world came from Java, Sumatra, and the Malay Peninsula, until the Brazilian government started its great project of coffee cultivation by ubsidizing Italian immigrants, and thus opening up immense areas of coffee country. To-day Brazil controls the coffee markets of the world, and produces annually more than the world can consume. of the ruined coffee plantations in the F East, with thousands and thousands of acres of improved and cleared jungle, have planted rubber trees between the rows of coffee trees, besides clearing the land over great areas of the primeval jungle, and in the near future will reap the reward of their industry and enterprise. I was informed by a Dutch coffee planter in Java, that of forty-nine coffee estates of which his was one, forty-eight had practically failed and gone out of business as far as active coffee raising was concerned.

One incident of Dutch thrift in this connection notice on the trip home by steamer. came to my Being very III, I slept on the deck from Bangkok to At Penang we loaded on great quantities of coffee in bags, which had been shipped from Java and Sumatra for transportation to Europe and America. We arrived at Aden at the mouth of the Red Sea just after dusk of a beautiful tropical night. This port incidentally is a shipping point for Mocha, Arabiau, and Abyssinian coffee, which also incidentally brings a higher price than ordinary coffee. As I lay on the deck forward in my steamer chair, I saw that instead of loading coffee at this coffee port, we unloaded it in large quantities, on board of lighters lying alongside the ship. Later in the night the United States consulcame on board, going home with his wife, on leave to the United States. On being asked how much coffee arrived at Aden each day, he said about one hundred camel loads, and also now and then an Arab dhow from the African coast brought Abyssinian coffee in, but that great quantities were shipped out, amounting at times to thousands of bags, for which consular invoices were asked, and which was shipped mostly to America. He said he could not understand where so much coffee came from. Pointing over the side at the loaded lighters, I told him that there was his surplus coffee, and that the thrifty Dutch evidently believed in getting as good a price as possible, by unloading it in lighters and transshipping it to th next steamer. Java coffee became Mocha, and the shippers and the consignees had the consular invoices to back them up and show that the coffee actually ame from the port from which Mocha coffee shipped from Arabia; thus to prove the fact to any doubting buyer, who might want to investigate the great supply of Mocha coffee coming from the barren

Now to-day in Brazil the great problem in gathering rubber over the three million square miles of its rubber territory is conveyed in the one word labor; leaving out the great destruction of the wild rubber trees by the careless and unscientific gathering of crude rubber, also often the absolute destruction the trees. In the Philippines, Indo-China, and the Malay Peninsula the common habit of the native gatherers in the jungle is to cut down the big trees and to scarify the trunk when lying on the ground, thus absolutely destroying the tree; or as the Siamese and natives of Indo-China do in the great valley of Mekong, cut down and destroy the climbing vine, which there produces some of the finest rubber in the world. To-day, over an area of two hundred thousand square miles in the Mekong valley, the production and export of crude rubber has steadily decreased in the last ten years, and has now almost entirely ceased; Bangkok and Saigon being the two principal shipping ports, and most of the rubber going to France. This area of the Mekong valley is one-fifteenth of that of Brazil.

(Continued on page 468.)

HANDCUFFS: AND ESCAPES THEREFROM

BY HEREWARD CARRINGTON

One of the most interesting "acts" in recent years is that of the "handcuff king," who manages to escape in some manner from all sorts of regulation handcuffs, manacles, leg irons, etc. Several of these are placed upon him; and then the performer retires into his small cabinet, and emerges in a few minutes entirely free from all restraint. The cuffs are in every case genuine, and no confederates are employed. It is a very clever illusion.

There are several trick handcuffs upon the market, and, if the performer be allowed to use his own cuffs, they may have been tampered with. There are trick cuffs of various kinds. Some of these simply pull open, and are never properly locked. In some makes, the links of the connecting chain are "faked." In some cases, the lock fiself has been tampered with, so that a blow on the hinge serves to release it.

But we will assume that none of these prepared cuffs are used. Those of the committee are employed.

If these are of old makes, many of them may be opened with a loop of catgut or shoestring, inserted into the keyhole. This catches the lock, and jerks it back. The style of cuff known as the "German transport chain" is never really unlocked; the hands merely slip the chain, after certain manipula tions of the hands and Most padlocks are arms. merely picked with one or other of the numerous skeleton keys, with which the performer is sure to provide himself. French letter locks are opened by finding the proper combination. This is largely a matter of touch, facilitated by placing a wire spring between the arms of the catch, to keep them pressed well back. would be impossible to describe this feat on paper.

I now come to consider regulation handcuffs and the means of escape therefrom. In this connection it is hardly necessary to describe the various regulation leg irons, since the key which unlocks one make of handcuff will generally unlock the same make of leg iron.

If the performer is not to be searched, his task is comparatively easy. Keys may be concealed in his clothing, in various special pockets, or in the draperies of his cabinet. however, he is to be searched, more precautions must be taken. Special

keys are then concealed in a false boot heel, in the mouth, in the hair, or in a special false finger which the performer employs, and beneath which the "fake" is hidden. If the key is hidden in the hair, should be long and bushy, and the performer, after having had his hands examined, remarks to his con mittee: "Would you like to examine my hair also, and see that it conceals nothing?" he passes one of his hands through his hair with a careless motion, and thereby extracts the "fake," which he promptly conceals in one of his hands or elsewhere. A "fake" may also be concealed in the corner of a handkerchief, and in this case an opposite corner can be reached with the teeth. The "fake" being reached in this manner, the performer employs it to open the cuffs as described. There are many contrivances known as "fakes," which are used to open the lock of various handcuffs under conditions when it would be found impossible, even if the performer were in possession of the key, to use it. Goldstone has introduced an ingenious "fake" of this kind, with which the majority of English regulation cuffs (Figs. 5, 15) can be opened. An illustration is given herewith (Fig. 1). Mr. Goldstone says: "This new 'fake' is nothing more than a steel tube tapered, with a rod fitted through the center. By drawing atten-

are not level, a quarter of an inch at each end having been filed away. The tube does not contain any thread whatever. To open the irons, thrust the end of the fake into the lock, catch the spiral spring with the longest end of the tube, and then pull outward It will be found quite an easy matter to open cuffs and irons." It will be seen that this fake is used to It will be seen that this fake is used to force open the spiral spring, which is pulled out by its aid, the usual key opening it being that shown in Of late a new regulation key has been adopted in England, having the thread on the outside instead of the inside. This is shown in Fig. 3. The "fake" which is depicted in the same illustration (Fig. 3) will be found to open almost any cuff having this new improvement; the gradual diminishing size of thread enabling any cuff to be fitted, the key being simply pushed home until it accommodates the thread of the particular cuff used. It must be borne in mind

tion to both ends of this 'fake' it will be seen that they that handcuffs are of various makes, but that every

Coming now to consider various makes of handcuffs and release therefrom, it may be well to describe first of all one known as the "Bean handcuff." This is a cuff of American make, and when first patented was considered exceptionally safe. exceedingly difficult for the performer to reach the keyhole of these cuffs with the key, they have been fastened upon him. Yet when once Yet in presenting this trick, the performer not only has no dupli-cate key, but even allows the keyholes to be sealed, thereby showing that no "fake" or duplicate key of any kind is used.

The release in this case is effected by means of an ingenious "fake" depicted in the illustration. (Fig. 4.) This is inserted into the lock, and, being pressed home, forces back the spring catch. The catch being forced back, it can be slipped open almost instantaneously, and the release is effected. This is a favorite cuff, and one frequently employed because of the effect presented in allowing the keyholes to be

sealed. This Bean cuff must not be confounded with the "Bean giant," which in many respects is the safest and most perfect cuff ever devised. An illustration of it is given herewith. (Fig. 8.) If this cuff be locked upon the wrists with the keyhole away from the fingers it is impossible to open it, even with the aid of the key. The performer generally produces a decided impression by locking the cuffs upon some member of the committee, giving him the key and asking him to unlock himself. It will be found impossible

to do this. (Figs. 7, 11.)

In order to open the cuff, a "fake" may be employed, made as shown in the accompanying illustration. (Fig. 9.) It consists of a long strip of metal, to the end of which a key similar to the original is fastened, though of finer make. When the performer enters his cabinet, he gets possession of this metal strip and, holling the broad end of it between his teeth, he inserts the key into the lock and, by this means, opens the cuffs. If the cuffs are fastened with the keyhole away from the body, the some secure position, and

cuffs may be forced on to a key fastened in the woodwork of the stage, in the cabinet, or held in the cuffs are opened by being turned upon the key. Another important point to remember is that these cuffs are not properly locked until the two small knobs above and below the key-hole are pressed well home. If your committeeman does not know this it is poor policy to tell him, as escape from handcuffs is hard work at the best of

times, and is usually a race against time.

A very ingenious and complicated cuff, known as the "figure 8" or "plug" 8 handcuff, has been invented. The cuffs having been closed upon the wrists, they are fastened by means of a small screw or plug which is firmly screwed into the lock, retaining the pin, which faces through from the opposite side, as shown in the illustration. (Fig. 10.) In order to open these cuffs, it is necessary to unscrew the plug, then to insert the key, and turning first to the right, then to the left a number of times until the catch be released. An examination of the illustration will make this clear. In order to escape from this cuff, it is necessary, first of all, to unscrew the plug. This may be done by means of a "fake" held in the teeth, or by a more ingenious mechanism of a rather complicated nature, which may be inserted into the plug and, one of its wheels being held between the teeth, the other wheel is turned by means of the tongue, and this serves to unscrew the plug. If the hands be fastened behind the back, a (Continued on page 469.)



HANDCUFF DEVICES AND ACCESSORIES SHOWING THEIR USE IN METHODS OF ESCAPE.

cuff of a certain make is the same, so that the same regulation key will open all of them. Consequently, the same "fake" may be relied upon to open all of them. This is a valuable piece of knowledge, un-known to the public, which will be found of great use.

A new and ingenious "fake" has recently been devised, by means of which the majority of regulation handcuffs and leg irons, fitted with powerful springs, can be opened. The method in which this "fake" is employed is depicted in Fig. 2. A key is known as a "master key" when it will unlock two or more handpadlocks, or any other form of lock. Harry Houdini devised an ingenious master key, with which enabled to open almost any regulation handcuff of the English make. It is comprised of a regular key, split on one side, so that it could be fore open more or less to accommodate the size of the thread in the lock presented. Three or four split keys of this variety, of different sizes, fastened to-gether upon a common (ramework, would enable the performer to escape from almost any English regulation cuff presented to him. A specially long key, and a key having a left-handed thread, should also be included in the performer's outfit. An electric pocket lamp should also be added, as valuable when working in the cabinet, which is generally none too light.

A LOCOMOTIVE STAGE

A STRUCTURE THAT WALKS TO ITS WORK

The Piercy locomotive stage, which was invented in 1908, and first used in connection with some difficult marine work at Peterhead, Scotland, is a self-contained movable stage, which takes the place of expensive temporary staging or falsework.

It is built on shore, walks out to its work, and continues to walk as the work advances, standing

high above tides and waves and defying the storm. It saves time and money, and is available for many uses besides that for which it was originally designed.

The invention provides a rigid stage, of any desired shape, design, and strength, which rests firmly on the sea or river bed or hard bottom under silt or sand, but can be easily moved, without removing a single bolt or connection, forward, backward, sidewise, or in a curved path, Thourh so mobile, it is perfetly safe and rigid in all weathers, and is not affected by heavy waves, strong currents, or tides, or even by blasting or other disturbance directly beneath it.

This result is obtained

by supporting the stage on two or more independent groups of spuds, or posts, which can be raised and lowered, and moved horizontally. Normally, when work is proceeding or when the stage is made secure to weather a storm, all of the spuds are lowered until their feet rest on the solid bottom.

When it is required to move the stage, each group of spuds is successively lifted and moved horizontally, while the whole structure rests on the other group or groups of spuds. The horizontal movement of each scoup of spuds is made possible by the construction of the stage, which consists of two or more parts, which are capable of relative motion in a horizontal, but not in a vertical direction, and therefore support each other in any position. Each of these parts is provided with a number of spuds, which can be raised and lowered. The details of construction, the number, arrangement, and combination of the parts, and

for moving the stage is very simple and is placed on the stage. It may be operated, according to circumstances, by hand, or by steam, compressed air, electric, hydraulic, or other power. The accompanying photographs illustrate the construction and operation of two Piercy locomotive stages, which have been employed in the construction of two breakwater



Piercy locomotive stages at Whitby. Note footprints of nearer stage which is "walking."

piers at Whitby. The position is very exposed and subject to exceptionally heavy seas, so that very strong and expensive staging was required.

The estimated cost of ordinary timber staging for the two piers, each 500 feet long, was \$32,500, while steel staging would have cost \$35,000. The two locomotive stages cost \$18,000, and it cost about \$400 to move them to the work. It is estimated that it will cost \$50 to move each stage along its 500 feet of work and \$200 to bring back to shore. Allowing \$200 for maintenance and repairs, the total cost of the locomotive stages will therefore amount to \$19,150, or to \$13,350 less than the cost of ordinary timber staging.

The stages were arranged to span the foundations of the piers with a clearance of 3 feet and a side travel of 3 feet for the purpose of adjustment. The stride, or distance by which the stages can be advanced by one shift of the spuds, is 10 feet. Each

and 37 feet long. Each spud has at the bottom a heavy shoe and at the top a strong socket to receive the end of the steel spud screw. The spud screws are 21 feet long and 5½ inches in diameter outside the double thread of 1 inch pitch. These screws do not turn, but are moved vertically by brass nuts, 8 inches in length and diameter, keyed in the centers of toothed


wheels which are turned by endless screws.

Both stages were erect-ed on shore and "walked" out to the work. The west stage traveled 1,000 feet and the east stage 3,600 feet, yet the transfer of the former cost \$325, and that of the latter only \$175. because the spuds of the west stage were operated by rope drives from the motor, while each spud of the east stage was provided with an inde pendent electric motor of 71/2 horse-power, an arrangement which greatly increased the speed travel. At first, with flat shoes on the spuds, about 3 strides of 10 feet were made per hour. In deeper water, with the shoes re moved, the spuds sank from 10 to 18 feet in the

sand, and the speed of travel was reduced one-half, but when the crew had become expert and the stage was nearly in position, a stride of 10 feet could be made in 15 minutes. The rate of travel depends almost entirely on the time occupied in lifting and lowering the spuds, as the horizontal movements are effected very quickly.

Each stage carries an electric traveling conveyor with a capacity of 6 tons and a range of 100 by 32 feet. This conveyor runs on two sides of the outer frame of the stage. The girders of the other two sides are composed of top and bottom channel plates, 15 inches wide and with 4-inch flanges, connected by struts and braces. In these channels run four pairs of rollers, attached to an intermediate frame, called the rolling frame, which carries no spuds. One roller of each pair runs on the girder and enables the outer frame to support the rolling frame. The other roller





East stage at Whitby "walking." Note the lifted feet.

West stage at Whitey working in rough sea.

A LOCOMOTIVE STAGE FOR WORK IN HEAVY SURF.

the directions in which they can be moved, vary according to the character of the work for which the stage is designed.

With a few rollers, pulleys, ropes, and hand winches, and the necessary timber and bolts, a cheap stage can be constructed on shore, marched out to its position in the water, and subsequently moved from time to time as may be necessary. On the other hand, for large works, where a very heavy and durable plant is required, the most elaborate, mechanically perfect, and well equipped power-driven stages can be constructed, and moved, within reasonable limits, almost as ear

stage has 8 spuds, of which 4 are attached to the corners of an outer frame, 50 feet square, and 4 to the corners of an inner frame, 40 feet square. The steel frames are 33 feet high, extending normally from 3 feet above low water to 22 feet above high water. The spuds have a lift of 21 feet and extend 3 feet below the lower bracings when raised, and 24 feet below these bracings, or 57 feet below the top girders when fully lowered. Hence the top of the stage can, if necessary, be raised 57 feet above hard bottom, or 30 feet above high water, and the load lifted by the crane can be raised 12 feet higher.

The spuds are Oregon pine timbers, 16 inches square

runs under the girder and enables the rolling frame to support the outer frame. One pair of rollers is attached to each end of the two main girders of the rolling frame, which, in turn, form the tracks of four pairs of rollers, attached to the inner frame and running on and under these girders.

The relative motion of the inner and rolling frames is perpendicular to the relative motion of the rolling and outer frames, so that the inner and outer frames, with their spuds, can be moved horizontally in any direction, with respect to each other. Furthermore, the whole structure can be supported by either group of

(Continued on page 470.)

Scientamer

dred to

about

Eighty done f on the way be

dirt lev

should

Abou being u

Twelve four m

structio

time of

LARGEST CONCRETE OIL RESERVOIRS IN THE WORLD.

The two largest reinforced concrete oil reservoirs in the world are now being rushed to completion at San Luis Obispo, Cal., by the Union Oil Company. Each of the reservoirs is 601 feet inside diameter and 20 feet $4\frac{1}{2}$ inches high above grade. When filled, each of the two huge tanks will hold more than

1,000,000 barrels of oil.

The building of the tanks was started on June 27th. when the Weber-Duller Company broke ground for excavation. The contractors agreed to complete the work by October 28th, 1910, or forfeit \$100 per day for each day's delay beyond that time,

The undertaking marks the most important con-


struction work in the California oil fields during the present year. The huge gusher production in the San Joaquin Valley oil fields has rendered an increase of storage facilities the oil industry's most pressing necessity. Millions of barrels of oil are now stored in earth sumps or catch basins, and despite insurance the loss through possible fires or rains would be heavy.

The oil to fill the two concrete reservoirs will be piped to San Luis Obispo through the Producers' Transportation Company's 8-inch pipe line from Bak-ersfield, Coalinga, Sunset, Maricopa, McKittrick, and the Midway fields. The tanks will cost approximately \$250,000 each, making an investment of half a million dollars for these two huge storage systems.

The length of the pipe line which will feed to reservoirs is 200.21 miles besides the gathering up reservoirs is 200.21 miles besides the gathering systems in the different fields, which add an additional 200 miles to the length of pipe. When the reservoir are filled with oil the latter will gravitate from the reservoirs to a pumping station to be built at 8m Luis Obispo, and will be pumped directly from the station to the tank steamers at Port Harford, or a station to the tank steamers at Port Harford, or a station of the station of such other points as the Union Oil Company place discharge stations. When filled, the reservoirs may be drained and cleaned by means of a 12-foot by 13 foot by 8-foot sump hole in the center, tapering in the sump hole being at the rate of one to one hundred.

To build the tanks has required a small army

men and the equipment of a regiment. Three hun



Wall of the huge reservoir, partly constructed,




Steel reinferced concrete wall of the 1,000,000 barrel off reservoir.



Later trimming for walls of concrete oil



View of construction work on 1,000,000-barrel oil reservoir.



Constructing the 1,000,000-barrel concrete res

merican

dred two horse teams, three hundred teamsters, and about three hundred additional men are employed. Eighty thousand cubic yards of excavation has been done for each reservoir. This dit is being banked on the outside of the concrete wall with just the road-way between the concrete wall and the dirt. These dirt levees put outside are intended to act as fire walls

should a fire sweep toward the reservoirs when filled.

About one million and a half feet of lumber is being used in constructing the roofs and the supports. being used in constructing the roots and the supports.
Twelve thousand cubic yards of concrete placed with
four mixers and two hoists is being used in the construction. When both reservoirs are completed the
time occupied in actual construction will be about forty days per reservoir.

The walls of the reservoirs stand up in the air 20 feet high without back filling or any other support. They taper from an average thickness of three feet at the base to six inches at the top. The reinforced concrete principle of building walls of city skyscrapers is used, and 250 tons of plain, round steel reinforces the concrete walls. The concrete floor is two and one-half inches thick, reinforced with wire

The two tanks are not being built simultaneously. The floor of reservoir No. 1 was finished September 20th, when the mixers were taken to reservoir No. 2. The building of the two reservoirs follows the necessity of increased oil storage facilities in California, the independent producers of the San Joaquin Valley

having recently voted to increase their storage capacity by 15,000,000 barrels. Those independents who have not their oil under contract for a period of years will receive storage certificates which they may negotiate.

With these two huge tanks completed the Producers' Transportation Company and the Union Oil Company will be in position to close contracts for oil delivery to the largest maritime consumers. Delivery to the tanks through the eight-inch pipe line of the Producers' Transportation Company, from the San Joaquin Valley fields will take place at the rate of 25,000 barrels per day. With 2,000,000 barrels of oil in storage and the oil constantly in motion there will never be a time when any considerable number of the storage and the oil constantly in considerable number of the storage and the oil constantly in considerable number of the storage and the oil constantly in considerable number of the storage and the storage and the constant points at Port Harford cannot be easily leaded. ships at Port Harford cannot be easily loaded.



molds for concrete and reinforcing rods of steel.




ting steel reinforced concrete wall 20 feet 4% inches high for oil reservoir.



Steel reinforcements for walls of concrete oil reservoir.



Trimming for oil reservoir walls.



lank Farm near San Luis Oblaco, California.

CURIOSITIES OF SCIENCE AND INVENTION

THE FIRST AEROPLANE EXPRESS.

The first delivery of express matter by aeroplane that has ever been made was that of 10 bolts (500 yards) of silk, which was carried by Phil O. Parmales on his Wright biplane from Dayton to Columbus, O., on November 7th. The start was made from the Wright aerodrome at Simms Station, near Dayton, at 10:45 A. M., and the distance of 65 miles to the driving park, some 3 miles beyond Columbus, was covered in 65 minutes. The air-line distance from Simms Station to Columbus—62 miles—was covered




THE FIRST AEROPLANE EXPRESS

in 57 minutes, which was a rate of 651/4 miles an hour, while the 35.9 miles from South Charleston to Columbus were covered in 31 minutes—a rate of 691/2 miles an hour. The aviator was favored with a strong northwest wind, which increased his speed over the ground from 40 miles per hour-the normal speed of Wright biplane-to about 70 miles per hour at The 200 pounds of silk, which was valued at \$731, was quickly delivered to the home store of the Morehouse Company by automobile immediately after Its arrival at the driving park, and thus a striking demonstration of the possibilities of the conjunctive use of the aeroplane and the automobile in the delivery of mail and express was accomplished. The time made was very much less than is required by the ordinary express, as no more direct system of town to town delivery could be devised. The weight of the aeroplane complete, with silk and aviator, was 1,180 pounds, and during part of the journey Parmalee drove his machine to a height of 2,500 feet.

AN AMPHIBIOUS AUTOMOBILE.

Some time ago we described in the SCIENTIFIC AMERICAN an automobile which had borrowed from the aeroplane a new method of propulsion. The driving wheels were disconnected from the engine, and the motor was connected instead to an aeroplane propeller located at the rear of the machine. With this novel driving mechanism the automobile fanned itself along at a high rate of speed, and in a race with an aeroplane, succeeded in making a speed of a mile a minute. This same machine has since been used in another novel manner. It was mounted on a small float on the White River, Indianapolis. Wires connected the front wheels with the rudder of the boat, so that the craft could be steered by operating the steering wheel. With this simple arrangement, the craft was propelled at a high speed, beating all launches on the river. Owing to the fact that the thrust of the propeller was considerably above the drag of the boat,



ODD COMBINATION OF WATER, LAND, AND AIR MACHINE.

there was a tendency, at high speed, to force the boat downward, and the danger of sinking prevented the use of maximum power. With the propeller revolving at 600 revolutions per minute, the float sank until the gunwales were almost level with the water. To persons on shore, the automobile appeared to be skimming over the surface with no float beneath it.

BLACK LIGHTNING.

Amateurs who take the trouble to photograph discharges of lightning are sometimes astonished to find that some of the flashes show black instead of white. Two excellent examples of such "black lightning" are

published herewith. They have been selected from a collection photo-graphed by Mr. Franklin Henshaw at Little Rock, Ark., this summer. Fig. 1 shows a broad white streak of light with a number of black branches radiating from it. At one or two places, in the original, there appears to be the trace of a heavy black streak peeping out from under the edge white streak, as if the white streak were covering a black one. This discharge struck a building seven away from the photographer. The other photograph is a two-minute exposure, during which time there were several lightning discharges. One of them is perfectly white, the other white with a black border at each side, and still a third that is entirely black. The black-bordered flash has the appearance of having exploded in the air. The explanation of these dark flashes is that they were reversed by over-exposure. They were probably more feeble than the other flashes, and were taken first. As the plate re-mained exposed for the other and more brilliant

flashes, a reversal took place on the negative, due to over-exposure. This same effect has been produced experimentally by exposing a plate to an electric spark in a dark room, and then exposing the plate a second time to gaslight.

SIGNALS FOR AVIATORS.

Kipling, in his famous "Night Mail," speaks of lighthouses which guide his imaginary air vessels to safety. Perhaps the German Aerial Navy League was inspired



SIGNAL NUMBERS FOR AVIATORS

by his story when it proposed that special beacon lights be erected at certain points. The aviator of the future will certainly need some such guidance if he flies by night. He will also need something to guide him by day. Attempts have already been made in Germany, through the efforts of Dr. von Oechelhaueser, to provide signals. In his system countries

and provinces are designated by serial numbers, and towns by combinations of two letters. The tops of gas tanks, which are painted black, are especially suitable backgrounds for the large white characters of the signals. One gas tank at Dessau, in Anhalt, has been marked with the serial number of the province, 75, in igures 33 feet high, and another with the name Dessau in letters 13 feet high, with an initial capital letter 20 feet high. This name has been read distinctly, in not very clear weather, from a balloon at an elevation of 1,300 feet.

A somewhat similar plan was recently proposed by Réné Quinton, of the National Aerial League of France. As shown in the accompanying Illustration, his scheme consists in using numbers, each in-

dicating the aviator's distance from Paris, and his position relative to that city. The figures are to be placed on the ground, or on a suitable roof, and will always read from west to east. The first number indicates the distance north or south of the parallel of Paris, and the second the distance east or west of the meridian of Paris. Six figures at the most will be required. Often five, and even four, will cover most points in France. Experiments have been made to test the scheme from the Eiffel Tower, with such success that it is said the road between Issy-les-Moulineaux and Châlons is to be thus mapped out



Fig. 1.—LARGE WHITE FLASH WITH BLACK BRANCHES.



Fig. 2.—A BLACK FLASH AND A BLACK-BORDERED WHITE FLASH

for a breadth of five miles, this being the most traveled airway of France.

NEW METHOD OF HANDLING THE WOUNDED ON WARSHIPS.

Ordinarily the injured in a naval battle must be carried to the hospital quarters on stretchers as are the wounded in a land battle. In the latter case conditions have been improved by the use of ambulances where the field hospital is at some distance from the firing line. Probably because in war vessels the hospital quarters are so near the region where the actual fighting takes place, no special provision has heretofore been made to facilitate the handling of the wounded. It is a simple matter to carry the disabled man on a stretcher until one comes to the hatchways. It is impossible to carry a man down a narrow stairway without subjecting him to lurching and jogging motions that may be extremely painful. As a remedy for this evil the German navy has introduced a new method of conveying the in-



LOWERING A WOUNDED MAN TO THE HOSPITAL QUARTERS.

jured to the sick-bay. A canvas jacket or bag is wrapped about the wounded man and laced up snugly. The bag is provided with handles whereby it may be attached to a best and by which it may be lowered to the hospital quarters. This method has the advantage of being expeditious and quite painless as well.

AN AEROPLANE FREIGHT CAR.

The accompanying illustrations show the exterior and interior of a new freight can which has just been brought out in England for the transportation of aeroplanes (especially those of the monoplane type) from one part of the country to another. The car is provided with end doors which make it possible to load a monoplane, after the wings have been detached,

by running the body part of the machine in at one end. The wings can then be placed on edge against the sides of the car. Suitable straps (which can be seen in the interior view) are provided for holding the wings in place against each side of the car. The car is provided with a rounded roof in order to make it conform as closely as possible to the loading gage of the railroad, and thus to gain Shrewsbury River. His most hazardous trip, howwas one around the Battery, up the East River, and through Hellgate, to the Sound.

A HOME-BUILT TRACTION ENGINE.

An ingenious farmer at Spy Hill, Saskatchewan, has rigged up an engine which he uses for traction purposes, and also for various power purposes about



INTERIOR OF AEROPLANE CAR, SHOWING END AND SIDE DOORS OPEN.

EXTERIOR OF AEROPLANE CAR, SHOWING END DOOR CLOSED.

every inch of available space in height as well as width. It is expected that a number of cars of this type will be needed in order to fulfill the demands of the aviators for transporting their machines quickly from point to point when aviation meets are in progress throughout the United Kingdom.

UNIQUE WATER BICYCLE.

BY A. W. CUTLER.

A curious foot-power craft has made its appearance in the waters about New York, which, for lack of a better name, might be called a "water bicycle." It comprises three boat-shaped floats which support an iron framework similar to that of a bicycle. These

the farm. Living, as he does, away up in the north traction engine. Therefore, with this outfit, he per-

country, where towns are few and far between, this man, Mr. Scheil, has been obliged to depend upon his own resourcefulness and a natural mechanical bent to assist him in the construction of the machine. He bought a marine engine of 10 horse-power, and adapted this motor to do the work of a stationary engine. The engine was mounted on the base of an old steam traction engine. This improvised traction machine serves to draw his plows, seed drills, and harrows. Three plows, each turning an average of about a fifteen-inch furrow, a four-inch disk seed drill, and a two-section toothed harrow, are hauled by the hour, and can work about two acres of ground per The engine starts with the plow in the ground without any difficulty, unless the sod is exceptionally tough, but even under such conditions the engine pulls out its load after a little coaxing.

COMBINED LOCOMOTIVE AND CRANE.

There is nothing very novel in the combination of

a locomotive and crane. The most familiar combination of this sort is the wrecking engine, which is a powerful crane self-transportable to the scene of the wreck, and able to haul the cars necessary for bringing back the wreckage to the repair shops. Another common form of transportable crane is the type used in docking yards and the shipping yards of large manufacturing concerns. The accompanying illustration, however, shows a very unique form of crane combined with a locomotive, which is of German design. It consists of a switching man design. locomotive fitted with a saddle frame, on which is mounted a crane of the balanced or hammer type. This form of crane is not powerful enough for wrecking purposes, but is useful in freight yards where the locomotive may be employed in shifting cars and making up

trains, while the crane may be employed in hoisting freight to and from the cars. The crane is provided with a swivel mounting and is also capable of swinging through a small angle vertically. The advantage of this construction lies in the fact that the crane may be applied to an existing locomotive and hence is more economical than other constructions in which the locomotive is designed and built especially for the purpose.

At a recent meeting of the Transvaal Institute of Mechanical Engineers, the president referred to the steel industry which will shortly be started by the South African Steel Corporation, the Héroult electric furnace being used for the conversion of miscellan-eous scrap into steel. He expressed the hope that this



PEDALING UP THE HUDSON.

little floats are made of light cedar wood, and are

hollow. The construction of the machine admits of their being turned up on end and cleaned, or emptied

of any water that may have leaked in. The gear is like that of a bicycle and is connected by a universal

joint, to a shaft which carries a small screw propeller located between the two rear floats. The entire

machine weighs but seventy-five pounds.

In the great water parade at the Hudson-Fulton

celebration, the inventor, John Mitchell, pedaled his

curious little craft up the river between the "Cler-


mont" and the "Half Moon." Mr. Mitchell has pro-pelled the water bicycle up the Hudson as far as

Yonkers, down the bay to Coney Island, and up the




CLEANING THE FLOATS OF THE WATER BICYCLE.

forms the complete operation of plowing, planting his" seed, and harrowing. Of course, with work of this kind, it is necessary to provide the engine with some sort of governor. The governor was rigged up on the premises, and has proved to be very sensitive. It controls the throttle, and does not permit the engine to vary in speed. A spring is placed on the slip to vary in speed. A spring is placed on the slip governor, so that if the pull should happen to be too much, it would let go of the load as the speed decreases, and likewise when starting. As soon as the engine speeds up to an average of 350 revolutions per minute, the load is put on automatically. The outfit has proved to be very successful. It runs at a speed of from three-quarters to one and a half miles per




PECULIAR CRANE AND LOCOMOTIVE.

effort at local production would not meet with ob stacles in the way of suspicion and prejudice. "It is true," he proceeded, "that the total output of the South African Steel Corporation will be for a time dependent on the amount of convertible scrap available, but it will be in the interests of the company, and, indeed, the terms of its contract with the govern compel it, to spend a certain proportion of profits in experimenting on the reduction of our native iron ores. It is quite within the bounds of possibility that a true steel industry will be established in a few years' time, having as its bases, first, the enormous iron ore de in the country, and, secondly, the low-priced electric power that cheap coal and more economical methods of transforming it into power will render possible.



THE MARIND ENGINE MOUNTED ON THE BASE OF A TRACTION ENGINE



THE IMPROVISED TRACTION ENGINE AT WORK IN THE FIELDS.

RECENTLY PATENTED INVENTIONS. Pertaining to Apparel.

HAT.—S. NEWMAN, Cincinnati, Ohio. This invention comprehends a hat, the crown of which is slightly swelled for the purpose of avoiding pressure upon adjoining portions of the wearer's head, and to the provision of means for holding the sweat band gently against the wearer's head at the points in question but with a degree of pressure much gentler than that otherwise afforded by the nat.

COLLAR.-CLARA KAHN, New York, N. Y. This invention is an improvement in collars, and has in view a stiff shirt or waist collar for either ladies or gentlemen, which can be washed with less work or at least expense and take up less room than the conventional linen collar, yet present a collar with a linen or washable fabric facing.

Electrical Devices.

Electrical Devices,
THERMOSTAT.—R. H. Waite, Denver, Colo.
An object of the inventor is to provide a thermostat which may be used to close a circuit at high temperature, as in case of fire, and thus sound an alarm or close a circuit at a predetermined low temperature. In the latter case the device may be used to sound an alarm if crops are in danger of frost or to operate devices for starting sanders fires. vices for starting smudge fires

vices for starting smudge fires.

TROLLEY-WHEEL.—E. K. Harris, Canandalgua, N. Y. The special features of this wheel are such that a greater portion of the wheel touches the trolley wire than in ordinary metal trolley wheels, and the wheel formed of such material as to allow the wire to give a uniform contact irrespective of irregularities or projections along the length of the wire.

Of Interest to Farmers,

PREIT CLEANER AND GRADER.—1. W. PECK, Bradentown, Fla. The object of this improvement is to provide a device that will grade or sort the fruit into classes, according to size, and will afterward clean the assorted grades, each grade being cleaned by a device adapted especially for that size.

LOADER AND STACKER .- R. B. FULTON LOADER AND STACKER.—R. B. FLITON, Red Cloud, Neb. This machine is capable of performing efficiently the work of a number of machines heretofore employed for different though allied purposes. It thus serves not only sweep. It may be used as a manure or snow shovel, for loading baled hay or car corn, and many purposes involving elevation and trans-portation of material.

portation of material.

BEETHVE ATTACHMENT.—8. BLAGE, Erle, III. It is the object of the present invention to provide an improved means for raising or detaching the super from the body and removing it without seriously disturbing the bees and without danger to the operator. It is an improvement on a former Letters Patent of the U. S., granted to Mr. Blagg.

Of General Interest.

SHEET-METAL PIPE.—H. BIENEAUM, Rapid City, S. D. This pipe-section is adapted to serve as a stovepie or various other uses, and is so constructed that it may be enlarged or contracted in diameter to accommodate and receive other sections differing in size, and the aggregate length of two or more sections thus coupled may be increased or reduced by sliding one upon the other, telescopically. one upon the other, telescopically

DRIP-CUP FOR UMBRELLAS.—J. T BLUFF, Butte, Mont. The cup can be collapsed when not in use and offers no material ob-struction upon the staff of an umbrella and

struction upon the staff of an umbrella and can be quickly adjusted to receive the drip from a wet umbrella and easily emptied and read-justed to receive drippings or to be collapsed. RECEPTACLE FOR SPUTUM.—W. L. Gerre, Bellingham, Wash. This device em-bodies a supporting frame, a removable recep-tacle hung in the frame, sheets of paper pen-dent in the frame and receptacle or sides there-of, means whereby paper from a roll may be deat in the traine and receptacle or sides there-of, means whereby paper from a roll may be drawn into position for covering solled sheets, by the invalid or the nurse who may remove the paper and receptacle—on time to time and cleanse the latter for replacement in the

GYROSCOPE AND SPHERE.—J. F. O'Byrns, Contact, Nev. This invention relates to tops and more particularly to the gyroscope top and is a combination of this well known to a combination of this well gyroscope top and is a combination of this well known toy and an ordinary hollow sphere which in the invention is regarded as the earth. Resides providing an amusing toy, the object is to explain and illustrate to the child the mo-tion of the earth around the sun, giving the seasons, and its rotation on its own axis, giving the days and nights.

Heating and Lighting.

FIRE-KINDLER.—S. ISHII. Roslyn, N. Y.
This invention relates to fire kindlers, the more
particular purpose being to provide a kindler
of this kind having sultable form for attachment to gas fixtures, and provided with apertures through which the gas can escape into
and around the fuel in order to facilitate the
ignition of the same. ignition of the same

JEWELER'S AND DENTIST'S BURNER:-JEWELLER'S AND DENTIST'S BURNER.—
A. ZAREMBOWITS AND C. ZAREMBOWITS, New
York, N. Y. This invention has reference to a
burner to be used in the workshop of jewelers
and dentists, or in any other profession where
an easily adjusted flame is desired. The
burner may be quickly and readily adjusted to
give any one of a number of different flames, as
desired, and has many for holding the parts desired, and has means for holding the parts in adjusted pe

Machines and Mechanical Devices.

Machines and Mechanical Devices.

BELLY-ROLLING MACHINE.—E. R. Zehnes, Toledo, Ohlo. This machine rolls the bellies of pigs to make the meat firm and compact and to give it a better appearance, all of which is effected by an endiess belly carrier. A meat flattening roll co-operates with the carrier and is movable therefrom in pressing or fattening operation whereby to subject the belly to a uniform pressure, and means provide for driving the roll and means operatively concet with the driving means to maintain the elements of the latter in working engagement on any position of the flattening roll.

BENDING MACHINE.—E. T. PALMENBERG.

a my position of the nattening roll.

BENDING MACHINE.—E. T. Palmenberg,
ew York, N. Y. This machine is more espeally designed for forming hooks on the suporting rods of garment hangers and arranged
opermit a number of such rods to be acted
non simultaneously, with a view to form
ooks of uniform size and shape, and irrespec-

ROLLING-BALLS GRINDING-MILL.—L. HOFFMANN, Vienna, Austria. The material introduced on falling down first is encountered by the beating wings and thus broken and thrown against the stationary grinding surface. By action of the helical surfaces on the upper side of the revolving ball disk, the balls are not only thrown outward, but also upward and strike against each other and against the stationary grinding surface, thus comminuting very efficiently the material which they encounter and then fall again on the ball disk and so on. ROLLING-BALLS GRINDING-MILL .- L.

CYLINDER-MOUNTING FOR CARRIAGE-FEEDS.—C. P. Myrr, Houston, Texas. This invention pertains to mountings for carriage feeds for use with saw-mills and the like, and has reference more particularly to a cylinder mounting in which the steam or other fluid pressure cylinder, having a piston therein and a rod operatively connected with the carriage, a adjustable to equalize the wear resulting adjustable to equalize the wear resulting m the sagging of the piston rod.

METHOD OF SEAMING CAN HEADS TO METHOD OF SEAMING CAN HEADS TO AN BODIES.—J. HOHLAND and K. J. HALLE-LID, care of Rosenstein Brothers, 98 North oore Street, New York. The invention re-tes especially to cans which are to contain reserved food, and which it is desirable to



METHOD OF SEAMING CAN HEADS TO CAN

seam without the use of solder, but so that the cover may be stripped from the body easily when the can is to be opened. Both the can body and can head are formed with edge dianges that may freely move one within the other. The flanges are then doubled and jammed together to complete the seam.

SEWING-MACHINE ATTACHMENT .- J. O SEWING-MACHINE ATTACHMENT.—J. O SEYMAN, Hancock, Mich. The aim in this in-tance is to provide an attachment for prevent-ag reverse motion in sewing machines which any be applied to existing machines without interial changes, and which when the machine into in the actual operation of sewing will of affect the operation thereof in any man-per.

ner.

PUMP.—C. M. SMITH, Los Angeles, Cal.

The principal objects here are to provide a
pump which may be operated as a single actlag or as a double acting pump; to provide a
pump which may be operated by man, horse,
or engine power at will; to provide one wherein the flow is even and continuous without
culestion or break; and to newtide a pluseur. sulsation or break; and to provide a plunger ead whereby there is no suspension of the lifting action

Hardware and Tools.

RAZOR-STROPPING DEVICE.—W. II.
SHATTUCK, Bridgewater Corners, Vt. The aim in this case is to provide a device which may be operated on the ordinary strop, the razor blade holder being plyoted to pins secured to means the razor blade holder is moved to the means the razor blade holder is moved to the other side by the roller, when the movement is reversed.

ENTRIFUGAL PUMP.—G. E. Hanes and time. A coil spring pressing against the inner im. A coil spring pressing against the inner of the other will raise a large volume of water from a comparatively deep well without requiring a comparatively deep well without re

CLUTCH.—H. W. LLOYD, 1805 East Beaver treet, Jacksonville, Fla. The object of this Street, Jacksonville, Fla. The object of this ciutch is not only to transmit motion from a driving to a driven shaft, but to vary the speed of transmission without intermeshing gehrs and without any break or interruption in changing from one speed to another. The clutch is provided with a chamber, in which a liquid is confined, and the liquid is circulated when the driven member rotates at a lower speed than the driving member. By controlling the rate of flow of the liquid the relative speed may be varied at will.

MACHINE FOR MILLING SLICING-KNIVES.—V. E. Dobbs, No. 12 Akazienstrasse, Kothen, Anhalt, Germany. The present inven-tion has reference to an improved machine for use in milling the grooves in slicing knives such as beet slicing knives and in particular on what are called roof ridge knives, that is to say knives in which their continuous ribs are knives in which to formed on the ridg grooves one from the ridges separating the separate m the other.

Pertaining to Recreation

FISH-HOOK.—J. Y. PAYTON, Waldron, Ark. This inventor provides a book which will move forward into the mouth of the fish when the forward into the mouth of the fish when the latter is taking the built, and hence will be more liable to engage the fish than will the ordinary hook. An operative mechanism is provided to accomplish this result, the mechanism being incased in a short protecting tube and guard and not liable to be broken by catching on weeds, rocks or projections.

ARTIFICIAL BAIT.—E. L. Cox, Alamosa, Colo. The bait is in form of a buoyant body, practically indestructible and has the shining surface of the natural insect or minnow. The urtace of the natural insect or minnow. The ody of the bait is covered with a quill and he quill is bound about the ends of the body o keep out the water, the body or inner surface f the quill being perfectly colored to imitate he insect or other bait which it is supposed to

Railways and Their Acces

METALLIC RAIL-FASTENER.—LETITIA FINDLE RAIL-FASTENER.—LETITIA Findlay, Ohio. The purpose here is to en shock and vibration incident to the deaden shock and vibration incident to the wheels of the rolling stock by interposing between the metallic supporting block and the ablock of wood or other suitable material, the wooden block being preferable, let into a groove formed in the upper face of the block and extending lengthwise of the rail, and the angular spike openings being partly formed in the block, which prevents the spikes from becoming loose by expansion and contraction of block, which prevents the spikes from be-ning loose by expansion and contraction of

PORTABLE TRAMWAY .-- O. F. HEYDES PORTABLE TRAMWAY.—O. F. HEYDEN REICH, New Orleans, La. Among the principa objects which the present invention has it view are: to provide a mechanism whereby the operation of the tramway is simplified and facilitated; and to provide a mechanism for operating the carrier to automatically arrest the same in adjusted positions.

CONCRETE RAILWAY-TIE.—R. J. D.
COWAN, Greenville. Mo. This invention furnishes a novel construction of tie and the clamps or yokes for securing the cushioning rail seats permit of the cushions being fitted loosely therein, thereby providing for expansion of rail and allowing the vibrating motion desirable for the preservation of the rolling stock. The plates are embedded with no parts expansed thereby relonging the life of the tie. exposed thereby prolonging the life of the tie

Pertaining to Vehicles.

SPRING WHEEL.—James A. Wille, Oak-dale, Pa. With a view to overcoming tire troubles on automobiles, Mr. Wible has de-signed a wheel within a wheel, that is, a wheel with a separate rim, the outer rim hearing a solid tire, being conn cted to the inner rim by



means of leaf springs. In order to keep one rim from creeping with respect to the other, the spokes of the wheel are made hollow, and are fitted with plungers connected to the outer rim. A coil spring pressing against the inner end of the plunger assists in giving the necessary resiliency.

coming from the differential which receives the drive from the engine in any convenient manner, and is mounted in a box of casing fixed to the chassis or frame of the vehicle, the shafts entering freely within the barrels and driving outside their central planes the wheels mounted upon the barrels.

wheels mounted upon the barrels.

BADDLE-SUPPORT.—E. H. PINKHAM, New York, N. Y. In this invention the improvement is on cycle saddle supports, more especially for motor cycles, and the inventor has in view a yielding support with which the saddle moves rearwardly and is depressed at both the front and the rear under shock, and is returned forwardly and raised by the result to porturally resident. wardly and raised by the recoil to normal posi-

MOUNTING FOR MOTOR-CYCLE SADDLE. MOUNTING FOR MOTOR-CYCLE SADDLE.

—8. Busch, New York, N. Y. Among the principal objects in view in this case are: To provide means for adjusting a saddle to the various positions desired for riding; to provide a construction and an arrangement of springs which form a sensitive and graduated cushion, and provide a construction which is strong and durable.

VALVE.—G. SCHUSTER, Besztereze. VALVE.—G. Schuster, Besziereze, Austria-Hungary. In the present patent the invention is an improvement in valves for pneumatic vehicle tires, coshions and other air-inflated articles, and it has for its purpose the prevention of possible leaking of the air the prev gh the valve after the article has been inflated

SPRING-TIRE.—V. A. MARSH, Endicott.
Wash. This inventor provides a spring cushion
for ties to yield to inequalities of the roadbed
while preserving the circular shape of the
tire; provides a cushion having a series of tire; provides a cushion having a series of communicating separate spring members ar-ranged to yield individually and to transfer a proportion of the compression strain; pro-vides means for excluding dust and grit from access to working members; and provides a wearing shoe constructed from material adapt-ed to grip the road bed.

VEHICLE-WHEEL .- O. TREIER, New York. VEHICLE-WHEEL.—O. TREIER, New York,
N. Y. The purpose of the present invention
is to provide a new and improved vehicle
wheel, more especially designed for use on
automobiles, bicycles and other vehicles, and
arranged to readily yield and to cushion the
vehicle. The wheel can be readily and conveniently repaired whenever nece

Note.—Copies of any of these patents will be furnished by Munn & Co. for ten cents each, Please state the name of the patentee, title of the invention, and date of this paper.

Legal Notices



INVENTORS are invited to communicate wit Munn & Co., 361 Broadway, New York, 62.5 F Street, Washington, D. C., in regar to securing valid patent protection for their in to securing valid patent protection for the ventions. Trade-Marks and Copyrights registered. Design Patents and Foreign

secured.

re Opinion as to the probable patents
an invention will be reauly given to any
r furnishing us with a model or sketch and
description of the device in question. Al
incations are strictly confidental. Our
Book on Patents will be sent free or Hand-Be

est.
rs is the Oldest agency for a established over sixty-five

MUNN & CO., 361 Broadway, New York Branch Office. 625 F St., Washington, D. C.

INDEX OF INVENTIONS

For which Letters Patent of the United States were issued for the Week Ending November 29, 1910,

AND EACH BEARING THAT DATE See note at end of list about copies of these patents.]

	Abdominal supporter and catamenial sack, combined, R. H. & M. L. Keagy	976,88
	Acid, amid of B-B diethylpropionic, L.	277.0a
	Adding and subtracting machine, W. Schooling	977,33
	Air and producing ozone, means for filter-	
	ing, S. C. Shaffner. Air and producing ozone, means for filter-	
	ing, Shaffner & Hutton	
	Cass Air heating, Westinghouse & Gow	976,967
	Airship, T. S. Harris	976,873
	Alarm system, central energy electrical temperature, Goldstein & Pool	977,296
	Alarm system, electrical thermostatic, A. Goldstein Amusement apparatus, W. W. McFarland	977,295 976,896
-	Anchor bolt, lead packed G. E. Rohmer Annunciating apparatus, electric, H. J.	977.112
İ	Althor	970,836
ı	Arch support W P Los	976.888
1	Antomatic Inhelector & Discrete	976,922 977,215
	Automobile signating device, W. G. Naon.	a column

DECEMBER 104 - 2			
Ayle Dunklin & Marley 976,85	Drills, tool dropping apparatus for, H. Kirk 977,409	Mechanical movement, A. F. Victor 976,953	Shoe supporting jack, L. G. Freeman 977,180
and saddle car, E. L. Sharpneck, 277,133	Prop Dox, coin operated, S. J. Kelly 976,884	Medical eye cup, J. S. Fox	Skiling, making, T. J. House 977,012 Sign, electric street indicating, J. W. Ellis, 977,081
Axle, independent car, C. B. Determen 977 280	Drving apparatus S Wiehe 077 244		Sign holder, W. H. Sweatt. 977,343 Signaling system, electrical, C. H. Pool 977,219
Axle intricator. Emerson & Feteral 977,308 Backboard, J. B. Horton. 977,130 Baking iron, G. N. Smith. 977,124	Drying roll, Lamp & Stiner	Metali, composition of matter to be used for the purpose of fluxing, M. P. Jewett 977,406	Sur mouth, obtaining, Baumann & Diesser, 219,211
Banjo, Rengert & Schwandt	Electric cut-out, B. M. Walpole, 977 658	for the purpose of fluxing, M. P. Jewett 977,406 Mining drill, water power, C. A. Hanson 977,302	Skinding and splitting cattle and scribing
Bark clock, W. E. Lowd. 977,378 Barrette, Farrell & Dowd. 977,378 Baths, rose for shower, H. Heldt. 977,148	Electric drop cord adjuster, W. S. Hull 976,192 Electric furnace, J. Harden 977,303	Mining needle, P. F. Costello	hogs, machine for, J. Lance et al 977,317 Skirt shield, sanitary, S. W. Little 977,203
		Mop and scrubbing brush, combined, J. O.	Sled, motor, M. Meyerson
Bearing, 101111 W F Ade 977.255	other carriages, voltage regulated, J.	Beazley 977.064 Mosquito bar frame, folding, E. Syner. 978,950 Motion transmitting device, J. F. Fagen	Siugs or fastenings in stock, machine for inserting, G. A. Ambler
Bed spring raising device, C. M. Schwab 910,350	Electric machine, dynamo, W. H. Powell 977,220	Motion transmitting device, J. F. Pagen- darm	Snow melting machine, W. N. Lux. 977,109 Sole and heel plate, J. T. Clishum. 977,272
	Electric machine, inclosed dynamo, A. H. Wouters	Mouthpiece tubes, apparatus for making, J. 4	Moretacles, bridge connection for lenges for
Bin, Leibe & Bonnaffons	Electric switch, P. L. Sibole	C. Muller 977.394 Mower, lawn, R. E. Hedges 977.092 Music holder, C. G. Peterson 977,397	J. Savoie 977,227 Speed machine, variable, R. E. Rosewarne, 977,403 Spinning machine, cap. P. J. Moropey. 977,223
kowski	bard	Music sheet rolls for mechanical plano	Spiral separator, F. H. Blatch 976,980
Bollon S Prehandier 976.913	Electrical element, A. T. K. Estelle 977,086 Electrical equalizing system, R. Richter 977,328	players, automatically adjustable spool for perforated, H. G. Miller 977,030	Spiral separator, F. Pardee. 977,037 Spittoon, J. B. Pate. 977,218
Boller construction, A. B. Stirling . N. 1. 45, Mil. 144	Electrical equalizing system. R. Richter. 977.328 Electrical flasher, A. S. Gibbs. 977.294 Electrode, J. T. H. Dempster. 976,980	Musical instruments, pneumatic action for, W. F. Bayer. 977,259	Spring attaching clip, L. A. Young 976,973 Spring wheel, Z. A. & R. D. Bruegger 977,368
Boiler flue, J. R. Crowley	Flectrolysis of aqueous solutions, apparatus	W. F. Bayer. 977,259 Nipple cover, C. W. Ladley 976,887 Nut, axle, J. B. Wismer. 977,246	Sprinkler alarm and indicator, automatic, F. W. Milliken
Boot and shoe protector, C. B. Reese 977,398 Bottle stopper, G. Colucci	Electrotype plates, apparatus for backing, G. E. Dunton	Nut. lock. N. F. Chamberlain 976,847	Stalk cutter, J. R. Weatherly 976,959 Stallion shield, G. M. Frampton 976,863
Roy construction, folding, D. J. Rex 976,914	Elevator wheel, J. F. Barker 977,062	Nut lock, O. Salisbury 976,928	Stamp, addressing, T. Dillard 977,173
Box lid holder, M. Davidson	Embossing machine, C. Owens 976,905	Nut making machine, J. S. Hortman 977,011 Oil and gas mixtures, combustion of, H.	Stamps and labels, machines for affixing, ('.
Rrake mechanism, car, W. H. Durant 976,991	Engine indicator, internal combustion, E. D. Meier	Oil break switch, H. J. Hunsicker 977,193	J. Fancher et al
Brake mechanism for car trucks, H. W. Blake	Engine starter, F. C. Priestly 977,043	Ore and coal washer H. W. Faiker et al., 977.087	Stancion, cattle, J. B. Forwood. 977,289 Steam trap. M. I. Richards. 977,131 Stone polishing device, J. Ratcliffe. 977,327
Brake mechanism, automatic pressure con- trolling device for, H. Rowntree 976,925	Engines, variable exhaust nozzle for, Ham-	Ore screen, P. R. Stanhope 976,943	1 Stove and range construction. J. P. Mc-
Bread or other commodity catching device, G. Mueller 977,213	ilton & Twyman 977,301 Excavator, sewer trench, J. H. Johnson 977,016 Expansion bolt, G. C. Smith 977,232	Oven, baking, 8, Turner 977,347 Oven shelf, A. B. Kingsland 977,409 Oven shelf, Michael & McCarth 977,409	Donough Stove or furnace grate, W. Clerkin. 977,417 Straightening and hardening apparatus A.
Printle redorming machine E. Vogel 976 955	Explosion motor rotary F Beck 977.260		W. Machlet 976.801 Stuffing machine, R. & P. J. Brownson 976.882
Bristles, redeeming, E. Vogel. 977,037 Brooder, poultry, C. L. Cambridge 976,984		Pack opening apparatus, A. R. McArthur. 976,895 Padlock, F. Soley	Subway construction, E. B. Hess 977,304
Brush, air, T. A. De Vilbiss. 977,281 Brush holder, F. W. Reeves. 977,400 Brushes and the like, manufacture of flex-	Eyeglass nose guard, L. F. Adt	Panel board, R. H. Olley. 977,123 Paper drying apparatus, J. D. Tompkins. 976,948 Paper feeding apparatus, C. von Glahn. 977,146	Sucker rod elevator, A. R. Peters
Brushes and the like, manufacture of flex- ible tubes for fountain paint, G. Meyer, 976,899	Eyeglasses, L. F. Adt. 977,151 Faucet gage, cask, J. C. Newman 977,216 Feed regulator, C. E. Warner. 977,148	Paper feeding apparatus, C. von Glahn 977,146 Paper holder, roll toilet, A. B. & E. J.	for, P. H. J. M. C. de Gery. 977.383 Swimming bag, R. L. F. Berry. 977.065 Swing, A. W. Lyda. 977,200
Butter separator, W. B. Spencer 977,050 Buttons and button fasteners and coupling	Fence, L. S. Lachman, reissue	McEachron	
mechanism, feed tube for, G. E. Parker 977,124	A. Henning 977,180 Fence wire fastening, J. G. Hall 977,386	W. Dodge 977,376	Switch box, G. Gut
Cable carrier apparatus, J. T. Crowley 977,075	Fender, Seq Fireplace fender,	Paper, manufacture of wall, A. Trog 977,054 Paper stock, elimination of coloring matter	Telegraph system, G. E. Hines 977,008
Calculating machines, etc., full-stroke mech- anism for, W. W. Hopkins 977,190	Filing apparatus, W. T. Grady	from, M. H. Hubbard. 977,013 Pasteurizer, W. J. McKee. 977,029	G. Webster 976 061
Cam spout, powder, J. R. Hughes 977,095 Candlestick, miner's, G. Freeland 977,381	Filter, water, M. G. Melvin	Pasteurizing and refrigerating apparatus.	Telephone lines, central station call system for, W. E. Butler 977,067
Candy pulling machine, H. S. Brewington., 977,161 Cane stripper and topper, sugar, F. M.	Fireplace fender, S. B. Hays	combined, S. Shapiro	Thread selecting device, H. B. Colman 977,142
Cockrell, Jr. 976,850 Cant-dog, F. A. Cloudy 976,986	Flanged fitting end. E. F. Osborne 977,032 Flue cleaners, device for handling, M. O.	Photographic printing machine, J. J. Shater 377, 138	Threading device, left hand, H. M. Hunter. 976,880 Tie plate, A. J. Neafle 977,121
Car brake, emergency street, J. A. Gut-	Lewis 977,411	Plano tuning appliance, F. Huggins 977,004 Picker. See Cherry picker.	Tire, antiskidding, W. B. Yoder. 976,971 Tire clamp, B. Morgan 977,212
Car construction, F. W. C. Schniewind 977,089		Picture machine, moving, A. F. Victor 976,954 Pig handling apparatus, J. F. Schnabel 977,048 Pipe cleaning apparatus, gas, F. W. C.	Tire reinforcing fabric and making same,
Car construction, F. W. C. Schniewind. 976,932 Car coupling, H. C. Crigger. 977,373 Car door guide and guard, M. L. Cotter. 977,069	anism therefor, W. H. Cahall		C. Zeglen 977,357 Tobacco moistener, C. B. De Lane 977,374
Car equalizing mechanism, H. W. Blake 976,845 Car gate, J. W. Bussey 977,270	Folding box and crate, J. Biro	Pipe drawing machine, F. A. Schuster. 977, 236	Tobacco mold, carrot, A. La Chance 976,886 Tobacco pipe, J. B. McLaughlin 976,892
	Frames of every description, etc., founder tion for, A. van Rugen 97/,330	Pince annurates for clearing obstructions	Tolacco pipe, H. F. Schulte
son 977,310 Car, railway, Erwin & Tesseyman 977,405	Fruit conveyer, H. Hammond. 976,871 Fuel mixer, A. Schmidt. 977,229	from drain and other, W. Haddock 977,005 Plant thinning machine, J. W. Briscoe 977,162 Planter, corn, A. H. Leatherman 977,021	Towing machine, E. Dalgleish 977,277 Towing machine, Metcalf & Dalgleish 977,322
Car wheel, P. Holmgren	Funigator, O. Immermann. 977,312 Funnel, W. E. Crane. 977,372	Planter tension device, check row, E. W.	Tracks, making slotted tubular, R. Min- shull
strong, Jr 977,360	Funnel, J. Mathis 977,414	Player, automatic, W. R. Crippen 977.072	Traffic araters atreat E E Sincian 070 000
Cars, friction buffer for railway, J. F. O'Connor	Furrow opener, disk, To Brennan, Jr 977,367	Plow shock absorber, E. Barr	Transom lifter, etc., A. Fromhold 977,281
Carbon black together with combustible gas, production of, Frost & Nix	Game apparatus, base ball, A. W. Weeden, 977,149	Maclaren 977,110 Pneumatic despatch tube apparatus carrier,	Tray, crumb, A. V. Green. 977,185 Tray, folding, J. C. Toynbee. 977,239 Trolley, book E. N. McCall. 977, 249
Carbureter, Petersen & Pettit 976,911	Game, card, N. M. Hopkins	M. L. Emerson. 977,083 Pneumatic separator, F. A. Brenner. 977,100	There's weather to be an extensive and a series of the series
Carbureter, B. Rebourg	Gns and oil burner, combination, G. A. Smith	Pole and shafts, combined carriage, E. J.	
Carbureters, triple auxiliary air valve for, V. H. Donnelly et al	Gas fitting, W. Corbridge. 976,987 Gearing, J. H. Malley. 977,207	Holmes	Trolley pole, Robinson & Owen 977, 224 Trolley retriever, N. Peterson 977, 398
Carbureting apparatus, C. M. Kemp 976,885 Cards, playing, F. G. McPherson 977,117	Glass, apparatus for transporting and manipulating sheets of plate, L. De Bay 977,279	Post mold, L. H. Scott	Trombone locking device, H. C. Martin 977,026
Carpet stretcher, W. H. Metcalfe 977,210 Carrier. See Cash and package carrier.	Governing apparatus, H. L. Barton 976,839 Governing mechanism for fluid pressure en-	bar	Truck, electric, A. F. Batchelder
Cash and package carrier H. M. Weaver. 977,059	gines, H. H. Dow	curved, or tubular form, W. C. F. Papke 977,217	Trunk, chest, or the like, W. E. Smith 977.060
vording and accounting machine, M. P. Northon 977,393	Grass cutter, A. Euchenhofer 977,288 Grease gun, G. W. Stone, Jr. 976,945	Printing plate casting mechanism, stereo-	Truss, J. W. Kayser
Celtriold reds, manufacture of pointed, G. Petticollin 977,326	Grinding and polishing machine, F. Hayden, 976,875	Printing press inking device, D. W. Custer. 977,170	Tube cleaning apparatus, Robinett & Raid 1977
Chain or chain link, T. J. Williams 977,355	Grinding machine, F. Welker	Propeller for operating on fluids, B. G. Cooper	Tube cleaning apparatus, H. E. Weinland, 977, 341 Turbine blading, L. A. Haines, 977, 300
Chimney cap. E. J. Cochran	Grinding wheel, H. B. Nichols	Propelling mechanism, boat, W. L. Cramer. 977,169 Protractor, J. E. Smith 977,048 Pulley, friction clutch, A. S. Anderson	Turbine motor, T. J. Loftus 877, 107 Tweezers, E. A. Straub 977,341
Churn, J. E. Dinwiddie	Hammer manuar C D Floritum 0000	Pulley, friction clutch, A. S. Anderson 977,257 Pulp machinery, J. H. Wallace 977,147	Type and type bars, mechanism for mak- ing, F. H. Richards
Dykes Orkes Chute, Intercenting, W. W. & J. C. Dorssey, 976, 832 Clearette Upping machine, G. B. Hutton, 977, 015 Circuit opener, 4. C. Badeau, 977, 838 Clay and sand serven, A. W. Holl, 977, 609 Clock, alarm, W. J. Larkin, 977, 1977, 1987	Harrow, disk, W. C. King	Pulp machinery, J. H. Wallace. 977,147 Pump, air, W. A. Cook. 977,274 Pump, centrifugal, F. W. Krogh. 977,107 Pump Control of the Published Pump. 2017,107	Type case, supplementary, M. A. Stern Wit. 2009
Cigarette tipping machine, G. B. Hutton., 977,015 Circuit opener, C. C. Badeau, 976,838	Harvesting machine, D. J. Brower. 977,266 Hatch fastener, L. W. Young. 976,974	Pump, force, F. H. Richards	Typewriter ribbon reversing mechanism, au- tomatic, T. E. Buschmann 977,269
Clay and sand screen, A. W. Holl	Hatch fastener, L. W. Young	Pump, vacuum, A. H. Squier	tomatic, T. E. Buschmann 977,269 Typewriting machine, H. N. Josleyn 976,882 Typewriting machine, A. G. F. Kurowskii 977,019
Cock for air brakes, H. H. Westinghouse., 977,242	Richter	Pump, vacuum, A. H. Squier 977,338 Punch prees, muitiple, T. A. Banning, Jr. 977,362 976,877 Punching machine, C. F. Heinss 976,877 Puzzle, J. von Brethorst 977,265	Typewriting machine, A. G. F. Kurowski. 977,019 Typewriting machines, etc., time controlling mechanism for, Rice & Broughton 977,130
Coke, etc., apparatus for handling, W. C. Mitchell Coke oven and door therefor, F. W. C.	Richter 977,132 Hinge, W. H. Fromhart 976,999 Horse cleaning implement, B. Lobee 977,136 Horses, electric appliance for, J. P. 8an- bora 977,831	Rack. See Disdiay rack.	
Schniewind	born 977,331	Radiator, J. J. Lawler	Latta & Herrmann 977, 201 Typographic form, F. H. Richards 976, 919 Vacuum dust remover, Foster & Glidden 977, 380 Valve, T. F. Payne 976, 908
for, F. W. C. Schniewind 976,930	bora 977, 331	for, L. A. Girvin	Valve, T. F. Payne 976,908
Coke oven dscharging apparatus, F W C	Hydrocarbon burner, W. M. Green 977,186 Ice cream spoon, J. Geler 977,382		Valve, H. Lippoid 977,105 Valve fitting, J. F. Bernstein 977,201 Valve grinder and drill, combined, O. R.
Schniewind 976,934 Coke oven, regenerative, E. Wagener. 977,348	Ice scraper, G. B. Miller 977,211 Illusory dramatic effects, apparatus for	Rall Joint, H. A. Christy 975,985 Rall Joint, C. Lakosky 977,020 Rall Joint, G. Payant 977,040 Rall Joint, G. W. Robbins 977,045 Rall Joint, A. Daly 977,742	Angell 977,258 Valve remover, P. C. Wlest 977,245
	Illusory dramatic effects, apparatus for producing, T. R. Barrett	Rail joint, G. W. Robbins	Valve remover, P. C. Wiest 977,245 Vault, W. H. Hollar et al 977,307
Collars, spacing device for use with turned down, C. J. Kintner	Initiation device, E. De Moulin	Railway crossing, L. Alexander. 977,153 Railway, electric, R. P. Williams. 977,354 Railway, agre, W. E. Geddes. 977,001 Railway rail joint, S. Ferris. 976,890 Railway rail joint, S. Ferris. 976,890 Railway witch safety lock, J. R. McKinnis 977,176 Railway tte, metallic, W. D. Forsyth. 977,179 Rat tran W. S. Ward.	Vault, W. H. Hollar et al. 977,367 Vehicle brake, G. W. Flsher, reissue 15,175 Vehicle running gear, motor, W. Juneau 977,407 Vehicle spring sidayension, P. Morren. 977,392 Vehicle wheel 8 1 Simones 976,000
Color screen, H. E. Merwin. 977, 420 Combination lock, H. Hanflig. 976, 872 Concentrating apparatus, J. Matter. 976, 893	Internal combustion engine, E. Easthope, Jr. 976,858 Internal combustion engine, J. E. Sears, Jr. 977,334	Railway gate, W. E. Geddes 977,001	Vehicle wheel, S. L. Simpson 177,392
Concentrating apparatus, J. Matter. 976,873 Concrete piling, method of and sectional core for making, J. F. D. Withrow. 977,356	Invalid lifting apparatus, G. White 977,243 Ironing table, A. J. Foster 978,967	Railway switch safety lock, J. R. McKinnis 977,116	Vehicle wheel, S. L. Simpson, 17. Morren. 177,392 Vehicle wheel, S. L. Simpson, 176,288 Vehicle wheel, W. Q. Kennedy, 177,493 Vehicle wheel, cushion thread, H. C. Brown 377,493 Vehicle wheel, cushion thread, H. C. Brown 377,493 Vehicle paid, shield, C. D. Dann. 377,732 Vehicle paid, shield, C. D. Ban, 177,202 Vehicle paid, shield, 177,202 Vehicle paid, 177,202
-tourrete structures, apparatus for erecting,	Ironing table, A. J. Foster	Railway tle, metallic, W. D. Forsyth 977,179 Rat trap, W. S. Ward 977,240 Ratchet drill, F. E. Farley 977,176 Reschet drill, F. E. Farley 977,176	Vehicle wind, shield, C. O. Doan 977,174
Controller handles, locking mechanism for,	Jar wrench, fruit, Graffort & Hoffman 976,868 Key extractor, J. Kopietz 977,018 Key ring, J. A. Prigge, Jr. 977,221 Kilns, fuel burner for cement, M. F. Man-		Voting, device for independent, C. H. Ocum-
A. S. Cubitt. 977.073 Conveyer, C. D. Seeberger. 977.047 Conveyer, chain, T. A. Coleman 977,273	Kilns, fuel burner for cement, M. F. Man- gelsdorff	Razor strop, E. Hunold	paugh Vulcanizers, quick opening door for, J. K. Williams
	gelsdorff 977,113 Kitchen utensil, O. C. Berchtold 976,979 Knitting machines, casting-off bur for cir-	Refractory material, manufacturing, G. C.	Wagan brake I I Tomas oggan
ling for extensible, W. Lennon 977,023	Lacing hook setting machine, A. R. Hav-	Fludder et al	Wall set, A. H. Weiss 976,962 Wall socket, G. W. Goodridge 977,297 Warning apparatus, automatic trembler particularly applicable to, E. Teste 977,238
Corn husker, T. I. Ludwig. 977.205 Corset clasp, E. B. Howland. 977.390 Cotton chopper and cultivator, combined, J.	Ladle for popring molten metal J. W. Cal.	Reinforcing frames String for C M	particularly applicable to, E. Teste 977.238
R. Stovall	laghan 977.271	Graham	Wash bowl and basin trap. A. McIntosh 977,319 Washer. See Ore and coal washer. Watch movement, W. B. Mehl 977,320, 977,321
R. Stovall 977,340 Cotton chopper attachment, H. S. Berry 976,842 Cotton gip, W. W. James 977,194	laghan 977,271 Lamp, J. E. Allen 977,358 Lamp, electric arc. W. Legel 977,022 Lamp, inverted incandescent gas. P. Lucas 977,022 Lamp manipulator, incandescent, R. H.	Resilient wheel, L. F. Delaney 976,989	Watch movement ratchet mechanism W W
Cotton gin, W. W. James. 977,194 Cotton picking machine. J. F. Appleby. 977,155 Coupling. See Car coupling.	Lamp manipulator, incandescent, R. H.		Water and air proof composition of matter
Crank, extension, A. C. Zierath. 977,252 Crate, collapsible, H. B. Walter 976,958	Lamps, cooling vane for second-class glower, A. Kusebauch 977, 198		Mielck & von Heydebrand 977,423 Water gage, C. L. Dickerson 977,375
Crushing mill, T. J. Sturtevant. 977,235 Cultivator, E. M. Dowdy. 976,854	Berkstreaser of for second-class Cantern, R. J. Williams, cooling vane for second-class 177,198 Lantern, rallway, J. Wright. 977,251 Latch and catch for doors, combined, C. M. 977,137	Reversing mechanism, fluid operated rotary movement, G. A. Fowler	Water heater burner, J. Mulrhead 977,214 Water motor, H. W. Yost
	Sexton	movement, G. A. Fowler 976,998 Robe, automobile, J. P. Gordon 976,896 Rock drill, S. W. Brothers 976,981	Water motor, H. F. Blackwell 977, 264
Cultivator, B. L. Nebf. 977,031 Cultivator, B. F. Stovall 977,051 Cultivator replanter attachment, F. E.	turret, J. G. Oliver	Rock drill, S. W. Brothers	Wave motor, B. Cutler 976,988
Cultivator replanter attachment, F. E. Markley 977,115 Decorative leaf and making the same, J. A.	Leather wringing machine, R. F. Whitney. 976,968 Lever, C. A. Murphy	Rope, chain, or wire stretcher, J. S. Sourek 976,941 Rotary engine, J. Putman	Micick & von Heydebrand 977,422 Water gage, C. L. Dickerson 977,375 Water heater burner, J. Mulrhead 977,214 Water motor, H. W. Yost 976,972 Water motor, H. F. Blackwell 977,294 Water motor, H. F. Blackwell 977,294 Watering trough, B. Hasman, Jr. 976,874 Wave motor, B. Cutler 976,888 Weaner, calf. J. S. Weathers 977,378 Weighing and filling machine, H. Dankerly 977,378 Weighing apparatus, sutomatic, C. B.
C. Fichtmueller	ener	Rotary engine, J. Putman. 976,913 Rotary engine, H. A. Massey 977,027 Sad iron heater, W. H. Van Horn 976,952 Sand blasting, shield for hollow articles in, T. Buseko	Weighing apparatus, automatic, C. R. Hutchinson. 977.014 Wheel lock, bleyele or other, B. Schestopel, 977,228
C. Fichtmueller 976,694 Delivery machine, J. M. Beavo 976,978 Discharge and overflow fitting, G. Helbling, 977,304 Disinfecting apparatus, P. C. F. & C. 8.	Lingtone machines space hand buffer for	Sand blasting, shield for hollow articles in, I. Bucsko 977.268	Wheels, detachable and sections) rim for
Disinfecting apparatus, P. C. F. & C. S. Effantin 976,992	G. E. Wallin	Band pushing saired for bollow articles in 1. Business for bollow articles in 977,2647 and 977,247 Saich, cord fastener A. M. Woerner 977,247 Saich, cord fast for 1. Marchews 977,042 Saive affacthenet, C. W. wwwfon 977,052 Saw drag, M. L. Maxwell 977,052 Saw Johiter A. Stecker 977,233	vehicle, J. W. Miller 976,900 Wheelbarrow, H. M. Verplanck 977,056 Whistle, automatic warning, T. E. Kinney 977,017
Disinfector and deodorizer, J. Williams et	Laquid Auer Durner, Siequerry & Everett 916,898	Saw attachment, C. W. Newton. 977,415 Saw drag M. J. Maywell 977,000	Whistie, automatic warning, T. E. Kinney, 977,017 Winding apparatus, M. Leitch., 977,101
at 977,353 Display box, E. H. Heppe 977,305 Display cabinet. A. T. Duncan 977,080	Liquids, apparatus for storage and delivery	Saw drag, M. L. Maxwell 977,028 Saw jointer, A. Stecker 977,233 Saw tool W Wakley 978,036 978,036	Window bracket, J. N. Parrahm 977,039 Window tent, J. G. Allen 977,154
Display card. R. Gair	Liquids, tank for settling, filtering, and	Saw Jointer, A. Stecker. 977,233 Saw tool, W. Wakley. 976,956 Saw trimer, rotary, F. W. Albrecht. 977,236 Sealing machine, carton, W. A. Joplin. 977,097 Scale to anchine the same transfer.	Winding apparatus, M. Leftch. 977, 104 Window bracket, J. N. Parrahm 977, 639 Window tent, J. G. Allen 977, 154 Window ventilator, A. A. Matheson. 977, 413 Wire clamp, D. P. Page. 976, 906 Wre cord, spring grip holder for, C. L. Glynn G. 1077, 204
Display device, B. W. Norton	Lock, V. G. M. Eras	Seals to packing cases, means for attach-	Wre cord, spring grip holder for, C. L. Glynn
Displayer, portable fruit. W. F. Crandall 977,063	Liquid shaker, N. Christensen. 977,165 Liquids, apparatus for storage and delivery of inflammable, R. Hausdorf. 977,188 Liquids, tank for settling, filtering, and collecting solids from, J. E. Rothwell. 976,923 Lock, V. G. M. Eras. 977,085 Lock, F. Kuba. 977,181 Locomotive boller superheater, W. Stephan. 977,384 Locom jacquard mechanism, W. Pearsail. 976,309 Looms, false reed for, J. C. Kaemfer. 977,313 Locoms, false reed for device for automatic	Separator See Rutte: separator	Wire petting, machine for weaving A W
Ditching tool, W. W. Wolary	Loom jacquard mechanism, W. Pearsall 976.909	Separator feed apparatus, spiral, F. Pardee, 977,038 Separator plate, apiral, F. Pardee,	Storey
Ditching tool, W. W. Wolary 976,970 Door and step operating mechanism, com- bined, H. Rowntree 976,926	Looms, false reed for, J. C. Kaemfer 977,313 Looms, stop-motion device for automatic	Senarators retarder for materials in united	A. Swindler 977.227
Door, metallic, G. B. Breakey 977,366 Door securer, J. Kohn 977,316 Door for silos, F. J. Van Cott 976,951	reshuttling, J. Rostran	F. Pardee 977,036	
Door, grain, E. Posson	Machine wrench, E. T. Ladd. 977 103	Shade making machine, window, R. W.	A printed copy of the specification and drawing of any patent in the foregoing list, or any patent
Door holder, C. T. Rogers	Mashing process A T M Leache 977,290	Tucker	nished from this office for 10 cents, provided the
Door, grain, E. Posnot. 970,891. Door, grain, E. Posnot. 977,042 Door holder, C. T. Rogen. 977,042 Door holder, C. T. Rogen. 977,042 Door securing methanism. H. Rowntree. 976,222 Door securing decision. B. Fuchs. 977,182, 077,183. Draft decision. B. Fuchs. 977,184.	Massage vibrator, A. E. Ellis 976,993	& McQueen 977,363	date be given. Address Munn & Co., Inc., 361
Draft device, E. M. Drady	Measuring current in three-phase systems,	Sharpening device, rasor, A. De Vivo 977.172 Sharpening machine, rasor, W. F. Rundel 976.927	Broadway. New York. Canadian patents may now be obtained by the in-
furniture, W. F. Wagner 977,349 Drill. See Mining drill.	Massuring current in three-phase systems with the phase systems of the p	Sheet metal tubes, machine for making, F.	ventors for any of the inventions named in the fore- going list. For terms and further particulars address Munn & Co., Inc., 361 Broadway, New
Drill attachment, Brown & Pittings 977,267	976,916, 976,918	Shoe cleaner, Haw & Southee 977,150	York. Munn & Co., Inc., 361 Broadway. Now
,			



For Foot Lathes

SENECA FALLS MFG. CO

THE SERASTIAN 15-INCH ENGINE LATHE their work. Catalog fro Ivert St., Cincinnati, Oh



GUNSMITHS, TOOL MAKERS, EXPERI-MENTAL & REPAIR WORK, ETC.

From 9-in, to 13-in, Arranged for Sta Foot Power, Velo or Stand-up Treas Send for Lathe C W. F. & JNO. BARNES CO



A Desirable Holiday Gift DRAPER'S Recording Thermometer

THE DRAPER MFG. CO. 152 Front St., New York





Nulite Gasoline Table Lamp

AGENTS-

CHICAGO SOLAR LIGHT CO.
212 So. Jefferson Street CHICAGO

YPEWRITERS MAKES



Visible Writers Olivers, Remingtons, Smiths, etc., Shipped ANYWHERE for Free Trial, or RENTED, allowing RENT to APPLY. Prices \$15.00 up




I Made \$15 a Day ling Metallic Signs What can do

METALLIC SIGN LETTER CO., 438 N. Clark St., Chic.



GASOLINE ENGINE '76 For Farmwork, Irrigation or Pumping, Factory and and Electric Lighting.

GRAY MOTOR CO. 121 Leib St., DETROIT, MICH.



Out on the pole on the roof, factory, mine or at hor it fills the bill. Our booklet on request,

EMMELMANN BROS. MFG. CO. INDIANAPOLIS, IND., U. S. A.





980 USE GRINDSTONES P go we can supply you. All sizes numbed and unmounted, always prin stock. Remember, we make a prin stock acting stones for all apering stones are stones. CLEVELAND STONE CO. or, Hickex Bidg., Cleveland, O.



Hayes Rubber Company

"Star" Large line of Attachmenta PLYING MACHINES, LIVING AND LIFE-LESS.

(Concluded from page 457.) birds are sustained and even lifted by wind blowing horizontally against the inclined under surface of their wings.

No bird can rise from the ground of even maintain a constant altitude in the air without moving its wings, unless the direction of the wind is more or less

upward, as is often the case.
Sudden gusts, shifts of wind, and atmospheric eddies are great impediments to flight. Very few birds can struggle to flight. successfully against a tempest. The great soaring birds are less valiant in this re spect than is commonly believed. The stormy petrel is so named, not because it braves the storm, but because it gives warning of a coming storm by taking refuge on the ship. The albatross skims the storm-tossed waves, but it often rests on them, sometimes swims, and, if need be, even sleeps on the water.

In fairly calm weather the equilibrium of birds in flight is maintained by number of instinctive movements, which are perfectly adapted to the needs of the ent. The neck, as well as the tail, plays an important part in these maneuvers. Weiss and other experimenters have shown that the flight of a gull is made unsteady and even impossible by imprisoning the neck in a starched collar Most insects appear to make great use of the abdomen in maintaining equilibrium. Wasps employ the abdomen in alighting and in turning.

As a general rule, birds, in alighting, check their horizontal motion by holding the body, and the extended neck, wings and tail, nearly vertical, and insects effect the same result by bending the abdomen forward.

The sustaining surfaces of an a plane are analogous to the wings of a oaring bird, but while the bird propels itself indirectly by occasionally flapping wings, rising and then gliding obliquely downward and forward, the aeroplane obtains its horizontal impulse from a screw propeller.

Some beetles which are sustained by their rigid elytra or wing-cases, and propelled by a helical movement of their posterior wings, present a closer analogy to the aeroplane, except in form, and even in this respect they have been imitated by Dr. Amans, who is constructing a flying machine of ovoid form, balanced and propelled by small wings. It has been proved by experiment that bumble bees and other hymenoptera can be deprived of their posterior wings, and butterflies robbed of much of their wing area, without losing the power of flight.—Adapted from "Lectures pour Tous."

The Future of Rubber in the Far East.


(Continued from page 459.)

Now this is the history of native coolie labor in the jungle in the Far East, and no doubt the same thing follows in Brazil as far as the wasteful gathering and destruction of trees is concerned. In Brazil the scarcity of labor is conceded to be the great drawback in procuring crude rub-ber; where efforts to import labor have so far been an absolute failure, thus leaving the shiftless Indians to be practically the only labor available. This scar-city of labor does not exist in French Indo-China, Siam, Malay Peninsula, Java, and Ceylon. Labor is plentiful. Under English law the English planter can get all of the Tamil coolies from India he needs, and he also has the great Chinese Empire to recruit from. In Siam alone nearly one hundred thousand Chinese coolies come in each year, and they are the agriculturists of the co untry, a as the men who successfully work the great tin mines which supply the civilized world with tin. In Java the Dutch have thirty-five million Javanese coolies to draw on-an inexhaustible supply.

Knowing these facts, a parallel can be PRINT for YOURSELF drawn between the future supply or run-Cards. circulars, book, newspaper. Press 86.

Cards. circulars, book, newspaper. circulars, book, newspaper. press 96.

Cards. circulars, book, newspaper. circulars, book, newspaper. circulars, book, newspaper. circulars, newspaper. circl



The \$1500 Abbott Detroit In Many Respects Equals \$4000 Cars

HE Abbott-Detroit is the one fully standardized motor car sold at \$1500. standardized motor car sold at \$1500. The Vital Information You Need It equals in many features and in its ecord many cars sold up to \$4000.

Its painting and trimming specifications are parallel to those of any \$4000 car on the narket.

The Abbott-Detroit has Chrome Nickel satisfact Steel Construction in the transmission and rear axle with imported F. & S. Annular Bearings and Timken Roller Bearings.

The Abbott-Detroit has a complete electric light equipment of two electric head-lights and combination electric and oil side and rear lamps and Bosch High Tension or Splitdorf

We Cannot Mention Here All The Features You Should Know About

If we had the space to point out to you how every rt of the Abbott-Detroit has been brought to such a stage perfection that we find it impossible to make any imposements, we could make you an Abbott-Detroit en'husiast. We simply ask you, however, to consider this conclusive iddence of thoroughbred quality—that the Abbott-Detroit has wer failed to place in a race or endurance run and has detect some of the best cars built regardless of price.

Let Us Send You All

The Catalog of get more for your money than

We can show you a purchase that will be one of the rea ons, the genuine values of your en

Just Sign Your Name And Address To The Coupon

Then tear it out and mail it. We'll send you the Abbott-etroit Illustrated Catalog by return mail and prove to you at this is the car you want and must have just as soon as ou <u>realize</u> what a wonderful car the Abbott-Detroit car is, pecially at \$1500. And to Dealers wanting territory not already closed we'll be

glad to make our regular Agency Proposition. Our production and large contracts are closed. Prompt action is imp
PRICES—Model B, Fire-Pessenger Touring Car, Standard and M. 1800 F.O.B. Datroll. Bendiere, Standard Equipment, 81800 F.O.B. Datroll. Production Contract Standard Equipment, 81800 F.O.B. Detroll. Particle Comps, Standard Equipment, 81800 F.O.B. Detroll. Comps, Standard Equipment, 81800 F.O.B. Detroll. 2009. Standard Equipment Standar

Abbott Motor Company 121 Waterloo Street Detroit, Michigan "The Place for You to Sign"

Name		
Address		
aaaress	 	

Important & Instructive Articles on

IN THE SCIENTIFIC AMERICAN SUPPLE-MENT we have published in the past few years papers by some of the more eminent physicists and engineers on flying machines. No book thus far published is so complete and so authoritative as these articles. The range of the articles is wide, covering as it does the theoretical side of aviation as well as those more practical aspects which deal with the construction of machines. The following is a partial list of the more important articles which have appeared in the Scientific American Supplement; see special note below.

Nos. 1816, 1817, 1818, 1819, 1820, 1821 and 1822.
The Practice and Theory of Aviation. By Crover Cleveland Leening, A. M. This is the most compact paper on aeroplanes that has probably ever been published. Fourtees biplanes and monoplanes are described in detail, and illustrated with scale drawings namely, the Farman, Cody, Curtis, Wright, Voisin (old model). Voisin (new model), and Sommer biplanes, and the Antoinette, Santos-Dumont, Bleriot XII, Irade, Pelterie and Pfitzner monoplanes. The proper diemioning of aeroplane surfaces, as deduced by famous experi

No. 1713. The Wright Aeroplane. description of the old type of Wright biplane evation rudder in the front of the machine.

No. 1756. Louis Blériot and His Aeroplanes. ealize that Blériot's successful monoplane is the result of ten erilous experiment. In this paper will be found an instru-essful Bleriot monoplane, illustrated with diagrams and ph


No. 1766. The Farman Biplane. A complete description of the Farman biplane, with detail drawings of the box tail and vertical rudders, the manner of working the four allerons, hand and foot levers which control the machine, plan view and side elevation of the entire machine.

No. 1767. The Santos-Dumont Monoplane. An illustrated article describing the Dem mallest and one of the fastest machines thus far made. Sketches accompany the article, showing

No. 1582. How to Make a Gliding Machine. Full details and drawings which will enable a glider for \$15,00.

All these articles are profusely illustrated.

Each number of the Supplement costs 10 cents, mailed, and you can order as many sem as you wish. A set of papers containing all the articles above mentioned will be them as you wi ided for \$1.20.



ORDER FROM YOUR NEWSDEALER OR FROM

MUNN & COMPANY, Incorporated, PUBLISHERS NEW YORK CITY 361 BROADWAY

chona culture in the past century will be repeated in the history of rubber in When that noble Spanish this century. n, the Marquesa de Chinchon, noble both by birth and nature, went among sick beggars and prisoners in the jails in the city of Cadiz in Spain in 1562, giving those suffering from fever the red powder brought from Peru by returning Jesuit fathers and conquistadores, and Jesuit lathers and condustatores, and which was said to be good for "heating of the blood and all humours," little did she think that the cinchona tree from which quinine is obtained would go down to posterity named after her, but so it is. Cinchona rubra, red cinchona; Cinchona Mava, yellow cinchona.

This red bark soon achieved great re pute in curing malarial fever, and later in the seventeenth century, both the Dutch and English governments sent expeditions to Brazil to procure specimens to be planted in their colonies in the East Indies. Out of twelve varieties containing different proportions of the alkaloid quinine, the scientists of the expedition picked out the two or three varieties which were the most valuable, and these were carried to the other side of the world and planted there. To-day the plantations of Ceylon and Java supply the chemists of the world with cinchona bark from which to extract quinine and its allied alkaloids, and Brazil has sunk There is as much cinto second place. chona bark in the Brazilian jungle as there was in times past, but it is not wanted in competition with the other, which has practically supplanted it.

This is exactly what will happen in the next few years to the rubber which comes from Brazil. To one who has not been in the Far East for the past ten years, the change is marvelous and won-In Ceylon great areas of land being planted with Hevea Brazilien-Labor is plentiful and cheap. In Java the Dutch are energetically at work with their characteristic thoroughness, are bringing great tracts of jungle arable land into the active producthe great plantation of Para-with labor unlimited. In the Federated Malay States, especially in Selangor, in Negri Sembilan, Perak, Pahang, and Johore, enormous areas of jungle as well as great coffee and tapioca plantations are being replanted with rubber. In Kedah, Kelantan, and Tringannu, the three Malay states just ceded by Siam to England, also, the wor's is being pursued with great energy by large companies, and Malay and Chinese labor is plentiful. In Siam, and in the peninsula, both Siamese and Europeans are going into the business by wholesale. The French in Cochin China are looking into the matter of rubber cultivation to offset the loss of revenue from the desed amount of rubber gathered in jungle, and are looking to the cultiva-tion of Para rubber to do this. No place in the world is so favorable to the cultivation of Para rubber as is Ceylon, Java, and the west coast of the Malay Peninsula. Climate and conditions are ideal. In eight years or less trees are ready to tap, although the planters have to fight for what they get, as white ants and other enemies of rubber have to be combated with, as in other parts of the world.

It has been my lot to travel through the Federated Malay States, also in Siam from Burma to Indo-China, from west to east and from north to south, from within two hundred miles of the frontier of Yunnan in southern China to the Gulf of Siam, also across the frontier into Indo-China, in the course of a residence of five years in the Far East, so that I have had a wonderful opportunity to see what the jungle as well as the cultivated areas can do. This also applies to what I saw in Ceylon. On a recent journey of about twelve hundred miles, most of it made by horse and elephant, going to within a comparatively short distance of the southern Chinese frontier, I had the unique experience of discovering a expert knowledge, dexterity, persevertree which had never before been reportance, and the possession of certain MUNN & COMPANY, Isc., 361 Breadway, New York City

ed as yielding rubber. miles to the westward of the Mekon River, near the town of Mok Dahan in northern Siam, we traveled for two days through a magnificent teak forest, which grew at an altitude of from three to four thousand feet, in the foothills of the Himalayas. After leaving this teak for est we had a rolling country, with the valleys showing characteristic tropical egetation of bamboo and palm, and the higher ground showing mostly trees of hard wood such as rosewood and ebony the country being very much open like an English park. Being compelled to Being compelle ride an elephant on account of illner as I could recline in the howdah, I had an opportunity to notice particularly the regetation, as we traveled very slowly with a large expedition, there beins eleven elephants to carry the sick, and about six hundred men, including officials and soldiers, with H. R. H. Prince Damrong, Minister of the Interior of Siam, at the head of the party. As we journeyed along, I noticed my mahout, who was walking beside the elephant, every now and then cut the branches of a certain tree which I had never before and feed the elephant with them; while doing so, large quantities of a white juice ran from the cut ends. The elephants seem to be very fond of it. I procured some of the juice, and found it to be good rubber, and brought some of the branches and leaves home with me, carrying them for six hundred miles through the jungle. This tree the Laos people call Mai Chan. On arriving people in the United States, I sent samples of the leaves and twigs to the Agricultural Department at Washington for classifica Secretary Wilson informed me that the botanical experts of the Department had decided the tree was Ficus Rumphii, and that it had never before been re ported as yielding rubber; other trees of different species of Ficus also produced rubber.

About the same time a French traveler Tonkin, French Indo-China, discovered a new rubber tree some hundreds of miles to the eastward of where I was. I believe it to be the same tree, and that we both stumbled upon the same fact The tree is very similar in appearance to the Boh tree, the sacred tree of Buddhism. Of course the natives would not allow a Boh tree to be touched in any It is rather doubtful if this tree will be of much commercial importance

In conclusion I would say again that the jungle will have to give way to the plantation and that the key to the situation will be labor unless as may happen some genius may invent synthetically some substitute which will take the place of rubber. Stranger things have hap pened.

HANDCUFFS: AND ESCAPES THEREFROM. (Continued from page 460.)

variation of this method is used, consist ing in a small instrument, shown in Fig. 14. By placing the finger on the end of this device, and by turning the larger wheel with the thumb of the opposite hand, the plug, first of one cuff and then of the other, may be removed. After that, the "fake" is employed to unlock the cuff in the regular manner.

There are two varieties of "thumb cuff" in use—the old and the new. In both cases, the thumbs of the two hands are retained by this cuff, made just large enough to close over the thumbs. (Fig. 12.) The old style was fastened by m of a padlock, the release from which was by picking the lock. In the new style of thumb cuff, it is impossible to use the key when the cuffs are in posi-tion, consequently a "fake" similar to that used in the Bean giant cuff is em ployed-held between the teeth, inserted. and in that manner the release effected

It would be useless to detail the actual methods of procedure necessary in order to open every style of cuff presented to the performer. It is simply a case of



What more appropriate, acceptable, and enduring gift than a watch? Waltham has been the watch favorite of social as well as of business and industrial life for nearly three-quarters of a century.

has beauty to commend it, usefulness, reliability and integrity to make first impressions permanent. It is a watch that flatters the recipient and keeps the donor in constant and grateful recollection.

There is no more perfect specimen of watch making than the Waltham Colonial. Made as thin as it is safe to make a reliable time-piece, it is the last word in the watchmaker's art. At all JEWELERS, from \$50 to \$175. Write for handsome booklet, describing the various Waltham movements and learn the one best suited to your needs,

WALTHAM WATCH COMPANY,

WALTHAM, MASS.





VEHICLES OF THE AIR

By V. LOUGHEED

r Exposition of Modern Acawings. The most complete wightlon. Sit pages, 65 x 9% including working drawing Price \$2.75 postpaid. Sequiar.

ng the work of 20 men. Write to-W. SMITH GRUBBER CO., 15 Smith Sts. La Croscont, Mins.

Classified Advertisements

READ THIS COLUMN CAREFULLY, - You will find

MUNN & CO., Inc.

BUSINESS OPPORTUNITIES.

fuguiry No. 9173. Wanted, manufacturers of achinery for removing fibre court from cocoanut

\$2,00.00 - WE WILL LEND YOU \$2,000 UNDER certain reasonable conditions, and agree that you may repay the loan from the dividends on an investment which we will suggest. For full information, address Continental Commercial Co., 8t. Louis, Mo.

Inquiry No. 9175. - Wanted, manufacturers of a

COMBINATION window shade and lace curtain ban-er; no nails or screws in casing; attached in one min-a. A single, Will sell or rotalty or outright. J. N.

are. A winner. With a light and a read damper of the property
unities and matrix.

FOR SALE.—Patent No. 98,077. Pneumatic pad for trong orders, baued August 30th, 1993. Prients applied or in Canada and Mexico. For particulars address N. Sallman, Springfield, S. D. Inquiev No. 9202.—Wanted, to buy the Rose contain pen.

ountain pen.

PROFITABLE OFFORTUNITY.—For saic, patent f self-balancing Ship-Table -keeps an "even kee!" exardiess of ship's motion. Universally needed. ast profes. A. M. Gustarison, Box 7st, Risbee, Arisons. Inquiry No. 9303. Wanted, addresses of those can offer courmiline crystals in quantity.

who can offer tourmaline crystals in quantity.
FOR SALE,—Paten No. 886.03. Propeller for vessels,
ships, and air craft. Will produce greater effectoring
the state of the factoring of the state of the conposition of the state of the state of the conposition of the contenders and is worth half a million. To be sold for \$2.50,
For particulars address August Abilirecht, 610 filter
Ave., East End. Pittsburg. Pa.

Inquiry No. 9204.—Wanted to buy non-binding
seekth boider.

FOHEMAN—A good pontion in the country for thright man, Must now be holding a reasonable position in manufacturing teathers. Must be under 30 years of ability. Also state present salary. Applications confluential. Address Position, Box 773, New York.
Inquiry No. #205.—Wanted, to buy nicotine consumer fitting any pape.

sumer fitting any pape.

GET A REPTER PLACE—Uncle Sam is best employer; pay is bigh and sure; hours short; places permanent; promotions regular; vacations with pay; thousands of vacancies every month; all kinds of pleasant
work everywhere; no lay-offs; no pail needed; common
cducation sufficient. Ask for free Booklet 46, giving
full particulars and explaining my offer of position or
money back. Eart Hopstin, Washington, D. C.

Inquiry No. 9206, -Wanted, manufa

SITUATIONS WANTED.

Inquiry No. 9207. Wanted, names and addresses firms making star section iron and steel suitable for

gibtining rods.

PURCHASING AGENT.—Young man (36) with leven years' gractical experience in buying for a large naturacturing concern, desires position as purchasing gent. Address Experience Box 73, New York.

Inquiry No. 920%. Wanted, the address of the

WANTED.

Inquiry No. 9209. Wanted, names of ow

MEN seeking a future wanted in every town, absolutely the best and most appealing proposition ever offered. This is no schume or specialty proposition. In vestigate, Metaric Mfg.Co.,745-747 E.-9th St., Chicago, (ii) Inquiry No. 9210. Wanted, names of owners of eposits of pumice or volcanic ash.

LISTS OF MANUFACTURERS.

COMPLETE LISTS of manufacturers in all lines a plied at short notice at moderate rates. Small special luts compiled to order at various price timates should be obtained in advance. Add Muno & Co., Inc., List Department, Box 173, New Yor Inquiry No. 9211.—Wanted, addresses of par-who can ship over containing, vanadium, molypden

SALE AND EXCHANGE.

Inquiry No. 9314. Wanted, address of maker

of "Plako," a fastenine for ladies' dresses.

Isaniry Ne. 9215. Wanted, machine for producine a good finish on hammer and other handles.

Inquiry No. 9216. "Wanted, to buy a sewing machine having a very long arm for special work.

Inquiry No. 9217. "Wanted, to ham as and addrever of manufactures of machinery for shelline almonths and seasons."

Inquiry No. 2018. Wanted, the names and adverses of manufacturers of outsits for saiting almonds

and pennuta. Hearity No. 9219.—Wanted names and addresses of manufacturers of base, cartons, and olded and waxed spec for marketing sathed amonds and ceanuts.

Lagarry No. 9229.—Wanted, the names and addresses of monthscurers of plants for the preparation theorem of the proparation of the proparat

Ineastry No. 9227. Warred, names and addresses it owners of mice properties.
Ineastry No. 92222. Wanted names and addresses of owners of waite sities and denosits.
Ineastry No. 92225. Wanted, to buy machinery or making such of mile.
Ineastry No. 92225. Wanted, to buy a motor driven loor scrubbing machine.
Ineastry No. 92225. Wanted, a concern able to trind and polish hammers.
Ineastry No. 92226. Wanted, to buy a machine for aking dat sided poworn cakes.
Ingality No. 92227. Wanted, a power-driven saw Ingality No. 92227. Wanted, a power-driven saw Ingality No. 92227. Wanted, a power-driven saw

lagatry No. #227. Wanted, a power-driven saw resulting down pine trees twenty inches in diameter. Inquiry No. #228.—Wanted, to buy fabric fufting inchines.

'fakes." "skeleton." and "master" keys, and other instruments which the per former selects and employs in each case having to depend largely upon his re sourcefulness to effect his release

There is no "royal road" to becoming a handcuff expert, and constant work and a close study of lock picking, of the makes and construction of the various locks, handcuffs, leg irons, etc., is essen tial. One or two apparently sensational performances will greatly add to the ex pert's reputation, though they may comparatively easy in themselves. C such is the escape of the performer from handcuffs so fastened upon him that his right wrist is drawn back over his shoulder, and his left wrist up behind his back. (Fig. 6.) In this position he is apparently helpless.

As soon as the performer goes into his cabinet, however, he pulls upon the right arm and, by means of tugging and certain strain upon the left arm, su reeds in bringing it forward over his head, so that the hands are now in front In this position, they may be opened in the usual manner

It need hardly be said that the famou prison cell escape of which so much capital has been made, resolves itself merely into a lock-picking contest. If the performer can succeed in picking the lock by means of skeleton keys, "fakes," etc. The success of the experiment depends partly on the ability to conceal the ous "fakes" or keys employed so that they and partly upon the dramatic presenta-tion of the trick. Of itself it is not more remarkable than any other lock-picking experiment, though it appears to be so

A LOCOMOTIVE STAGE.

(Continued from page 461.) spuds alone, in virtue of the connection of the outer and inner frames by means of the rolling frame and the 8 pairs of

The rollers are 18 inches in diameter They turn on fixed axles, 3 inches in diameter, by means of friction rollers, 1 inch in diameter.

The first Piercy locomotive stage ever constructed accomplished in the deepening of the Peterhead fishing harbor, a task that had been pronounced impossi ble. It saved three years, \$35,000 and a heavy penalty by blasting and removing 8,500 cubic yards of solid granite rock under water in eight months at a cost of about \$20,000. The cost of the stage and equipment, except the boring plant, was about \$3,000. Previously eighteen months and \$15,000 had been spent on the removal of about 1,500 cubic yards of rock.

ance with the special character of the work, can be employed with advantage in practically all operations in and under of staging of any sort, and also on land applications it should be noted that a locomotive stage can be provided with floats or pontoons for quick transport and that an all-timber stage, with its spu raised, can be floated like a raft to its

Any sort of dredging or excavating machinery can be mounted on a locomotive stage, and would be superior to a float-ing dredge in swift tidal or other currents, in exposed positions at sea, or in rivers and harbors where mooring cables interfere with traffic.

For submarine boring and blasting a properly equipped locomotive stage pre sents the great advantages of independof tidal rise and fall and safety without removal, during blasting. For

A 2-Foot Model Aeroplane \$1



A study for the man, a source of delight for the boy. With an ironclad guarantee to satisfy or money refunded we are mailing postpaid a complete working model of the Bleriot, Demoiselle, Wright, Santos Dumont and Antoinette Aeroplanes.

These Aeroplanes are exact duplicates of the above

famous machines AND WILL FLY. Price \$1.00.

Curtiss and Farman Models under same guarantee, price \$2.00. Aviation is still in the experimental stage. Using our Model for observation and study will help you to perfect

AMERICAN AEROPLANE COMPANY, Singer Building, New York City

AN IDEAL CHRISTMAS PRESENT FOR FATHER, SON OR BROTHER Your Choice of these Three Premiums with One Year's Subscription to POPULAR ELECTRICITY MAGAZINE For \$1





PERFECT ELECTRIC ENGINE

Why Don't You Read Up On Electricity? Screw Driver Knife

apparatus, etc. Full of hints on business economy and efficiency.

Junior Section delights the boys. Gives yours a chance.

Wireless Club Membership Free to Renders; if free, with many other privileges. Special offer, \$1.00 a year 50), including the premium you select.

POPULAR ELECTRICITY MAGAZINE, 440 Commercial Building, CHICAGO for all

Holiday Suggestions in Useful Books

TWO INTERESTING AND INSTRUCTIVE BOOKS FOR BOYS

The Scientific American Boy By A. RUSSELL BOND

SGIENTIFIG AMERIGAN BOY

12 mo. 320 pages 340 illustrations Price \$2 postpaid,

This is a story of outdoor boy life, suggesting a large number of diversions, which asid from affording entertainment, will stimulate in boys the creative spirit. In each instance complete practical instructions are given for building the various devices.

This is a story of outdoor the conflowing a large and like its predecessor is brin full of practical suggestions. It is also written in story form which makes interesting as well as instructive to the various devices.



The Scientific American Boy at School

nical turn of mind can read these books without being inspired No boy with a mecha to try his own hand at making the devices

MAGIC, Stage Ulusions and Scientific Diversions, Including Trick Photography

Compiled and Edited by ALBERT A. HOPKINS

The work appeals to old and oung alike, and is a most attractive holiday book. The illusions are illustrated by the highest class of engravings, and the exposes of the tricks are, in many cases, furnished by the prestidigitateurs themselves. Conjuring, large stage illusions, fire-eating, sword-swallowing, ventriloqu mental magic, ancient magic, automata, curious toys, stage effects,



photographic tricks, and the projection of moving photographs, are all well described and illustrated, making a handsome vol. ume. It is tastefully printed and bound. Acknowledged by the profession to be the standard work on magic.

Octavo (7x10 inches), 556 pages, over 400 illustrations.

MUNN & CO., Incorporated, Publishers, 361 Broadway, New York

BUY THE LOWEST COST ENGINE MADE. Lowest up-keep cost

FAVORITE ENGINE. No engine made has so wide a range of use. YOU WILL MAKE A MISTARE IF YOU DO NOT WRITE US FOR INFORMATION. 1½ H. P. to 5½ H. P. single cylinder. 6 to 20 H. P. two cylinder. 30 to 50 H. P. four cylinder. State your requirements and get our advise, THE TEMPLE PUMP CO., Massafacturers, 417 West 15th St., Chicago, U. S. A. This is our 58th year.



A list of 3000 magazines, newspapers and clubbing offers-Unique in the subscription field because it offers almost every possible combination desired.

it is crowded with profitable-to-you-suggestions. You cannot afford to be with-

J. M. Hanson's is the largest magazine subscription agency in the world-known everywhere.

Absolutely reliable and the most prompt in the magazine field.

Save **Magazine Money**

If your magazine money is limited—if you want to take more magazines, newsyou want to take more magazines, news-tion from the earliest times. John, Lord papers, periodicals of any or every class you can do so without increasing your present expenditure.

Our long time contracts direct with publishers insure you this. Write to-day for our 1911 catalog—if you want to save on magazine money or increase your list with no greater expenditure.

Send for this FREE Catalog

A postal with your name and ad-

J. M. HANSON'S MAGAZINE **AGENCY**

240 HANSON BLOCK

LEXINGTON,

KENTUCKY

these and other reasons it greatly diminishes the time and cost of the work and will probably make possible operations, the cost of which has hitherto been pro-hibitive.

The locomotive stage also affords an ideal support for rock-breaking machines

and for diving bells.

The work of driving piles would in many cases be considerably cheapened and hastened by the use of a locomotive stage, which is greatly superior to a floating barge in rigidity, ease and accuracy of adjustment, and independence of currents, tides, waves, anchors and cables, and also offers advantages over cantilever or overhanging pile drivers resting on the completed portion of the

The construction of breakwaters in deep water and exposed positions is one of the most important uses of the locomotive stage, which entirely eliminates the construction of falsework and the attendant difficulties of driving piles and bracing under water in dangerous situa-A stage, carrying a crane capable of lifting 15-ton blocks off the finished work and setting them anywhere within a distance of 100 feet, would cost less than one-third the price of a "Titan," running on the finished work.

Similar remarks apply to the construction of outlying lighthouses and other works. In constructing caissons or other foundations in which the permanent work consists largely of staging, this staging could be made locomotive, built on shore, walked out to the site and, after it had served its purpose ing, the spuds could be driven down to form piles of the permanent work.

For salvage and wreck raising, where

ever the water is not too deep the locomotive stage offers the great advantage that it can work in rough weather, which the wreck might soon break up and become a total loss. The stage would be floated or barged to a point near the wreck, and would then raise itself on its spuds, and walk to the wreck.

On land, when some heavy plant must be moved along the work over boggy, rocky or very uneven ground on which tracks cannot be laid, the plant could be mounted on a locomotive stage, having spuds of suitable length.

Light locomotive stages could be ployed as temporary piers for landing troops and baggage. They would be con-nected with the shore by gangways, which would be constructed as the stage walked out

Locomotive stages would also form cheap and convenient piers for seashore resorts. At the end of the season they could walk ashore and thus escape the fury of winter storms.

Aerial navigation has had its fasina-John, Lord chanics as well as in theology, and speculated upon conveying men bodily to other worlds. In a tract on the "Discovery of a New World in the Moon, London, 1638, he suggests three modes of conveyance. The first is to fit wings to the body of a man; the second is to teach a large bird to carry a man, so he can ride "as Ganymede did upon an eagle"; and the third is plainly a "heavier than air" airship. In describing the latter, the good Bishop says; "I do seriously and upon good ground affirm it possible to make a flying chariot in which a man may sit and give such motion unto it as shall convey him through the air; and this perhaps might be made large enough to carry divers men at the same time, together with food for their viaticum and commodities for traffic. He also naively suggested that the construction of such a chariot was "no difficult matter, if a man had leisure to show more particularly the means of composing it." It will always be a source of regret that the prophetic Bishop could not have spared the time "to show the means of composing" the interesting subject of his imagination.





MACHINES Corlins Engines, Browers and Bottlers' Machiners, 14K VILTKI

MODELS & EXPERIMENTAL WORK.

Inventions developed. Special Machinery,
E. V. BAILLARD CO.. 24 Franklert Street, New York.

SOUTHERN STAMPING & MFG. CO. R. S., Nashville, Tenn

DRAWING MATERIALS
E. G. RUFHLE & CO., Manufacturers
Fulton Street, New York, N. S. A
We Be Repairing at all kinds of Interessents

RUBBER Expert Manufacturer Fine Jobbing Work

BABBITT METALS.—SIX IMPORTANT formulas. SCIENTIFIC AMERICAN SCIPPLEMENT 11235-Price 10 cents. For sale by Munn & Co., Inc., and all newsdeaters. Send for cartalogue.

M. P. SCHELL MFC. CO., bing Work. Models and Experimental Work. 509-511 Howard Street, San Francisco, Cal.

Experimental & Model Work



THE SOLUTION OF THE WOOD PRESERVING PROBLEM

TIMBERASPHALT

makes it possible to treat timber thoroughly a effectively at low cost.

"TIMBERASPHALT" costs ½ as much as Creosote, and ½ as much as other Coal Tar preparations. It is slower-running and not sus-ceptible to weather changes. It excludes moisture, seat and air, thereby preventing the attack of world ceptible to weather changes. It excludes mounted the heat and air, thereby preventing the attack of widestroying fungi. This insures the maximum of the timber under all conditions.

It may be applied by Brush, Open Tank of resoure Methods. Write today for detailed in n and prices.

THE WOOD PRESERVING DEPARTMENT INDIAN REFINING CO., Inc. General Offices: 307 First National Bank Building Cincinnati, Ohio



TIMBERASPHAL INDI

Learn Watchmaking

LEARN TELEGRAPHY matically—easily become expert. Price \$0.00
Catalog free. OMNIGRAPH MFG. CO
Dept. 16. 50 Cordand Street, New York

Magical Apparatus.

MASON'S NEW PAT. WHIP HOISTS Maufd. by VOLNEY W. MASON & CO., Inc.

MODELS I CHICAGO MODEL WORKS

American Homes and Gardens

CONTENTS FOR DECEMBER, 1910

Among the Foothills of the Canadian Rockies The Country Seat of Howard Henry, Esq., at Camp Hill, Pa.

By Francis Durando Nichols 455

The Art of Ornamental Orange Peeling

By Harold J. Shepstone 461 Home—X. Treatment of Decorations and Furnishings for the Home-

Fireplaces and Mantels, . . By Alice M. Kellogg 463 . By Theodore Langdon Van Norden 466

Old South Salem Artistic Wax Work . By Monica Bastin 470

A Group of Modern Houses Costing from \$1,800 Upwards 472-473

Handicrastsman-Leather Crastwork, By Catherine A. Jensen 474 Crafts that Children Can Do . By Mabel Tuke Priestman 475

Ostrich Farming as an Industry . . . By Newton Forest The Small Country House—A Dutch Colonial House Cost-By Newton Forest 478 ing \$2,150 Complete By Paul Thurston 480

A Craftsman's House Costing \$2,400 Complete

A House and a Garage

Second Prize won by James M. Hull, Esq., Hamilton, Ontario, Can.

Third Garden Prize won by M. F. Ault, Indianapolis, Ind. 491 The Editor's Note Book Correspondence

American Homes and Gardens for January Index for 1910 New Books

PUBLISHED MONTHLY BY MUNN & CO., INC. NEW YORK CITY 361 BROADWAY

PRICE 25 CENTS

"My Xmas present; say, but these are fine"

TOOPER'C SPRING NEEDLE KNIT UNDERWEAR

COOPER MFG. Bennington, Vt. 34 Main Street,

The Boston Garter grasps the leg and your half hose in a way that feels good and safe,

See that Boston Garren is stamped on the clasp.

WORN THE WORLD OVER BY WELL DRESSED MEN.

GEORGE FROST CO. MAKERS

Its Economy and Power Startle the World!

Engine Runs on COAL OIL at a Fraction of Oct of Gasoline.

The Kerosene Wonder—on 15 Days'
Trial—Direct From Factory

Incorporate Your PATENTS and BUSINESS in ARIZONA


STODDARD INCORPORATING COMPANY, Box 8000 PHOENIX, ARIZONA

CRUDE DIRECT

R. H. MARTIN, 220 B'way, New York.

YOUR SAFETY RAZOR BLADES





A good motor car asks no favors of the eather. The day has passed when owners of automobiles pack their cars in moth balls with the first descent of Jack Frost.

With the arrival of the bracing cold and snowy days, ninety-two per cent. of Chalmers owners put on windshields, tops, chains, gloves, warm coats and robes, and—"go to it." It's great.

With top and side curtains, warm robes and a "hot iron," any car is comfortable all winter long for all members of the family. People don't "wait till spring" any more to buy cars. An automobile is a twelve-month proposition, and as serviceable in saving time in one season as another.

In fact, in winter, when street cars are so often tied up, when they are always crowded and filled with bad air, is when many city dwellers appreciate their cars the most.

Who's afraid of a ride in the stinging winter air? Or who's afraid of a little battle with a snowstorm? Modern men are not mollycoddles because they refuse to wear iron clothes and carry a sword, and because they insist on a bath A drive to business with the therevery day. A drive to business with the thermometer below freezing is the sort of experience that makes you feel like whipping the stuffing out of your day's work and taking a fall out of your biggest problems.

The wisest buyers purchase cars in the fall and winter. Then they are ready for use when the warm days come to tantalize you into the

Figure out what the interest would be on the price of a car between now and next spring. Only the price of a good dinner. What is that compared to the service the car could render you in the meantime?

Besides, if you order now you are sure of having your car when you want it the most. There is always a time in the spring when everyone wants cars all at once. And many are always disappointed.

Leaving our own interests out of the question, we want to tell you frankly that if you are going to buy a 1911 car at all, now is the best time to place your order.

So far as Chalmers cars are concerned, they are built on a quality, not a quantity basis. A good many people who wanted Chalmers cars last year were disappointed, because they waited too long to place their orders. Our dealers are ready to show you the new models at your convenience. Catalogue R on request.

"It Runs with Eagerness"

That is what the owner of a Chalmers "Forty" said recent-ly, describing his car.

Chalmers "Forty" said recently, describing his car.

A telling phrase, that! It describes better than any we ever heard the peculiar charm of a "Forty." We could talk to you by the hour, giving you the statistics of this car, the cold, reason-why facts of it—bore and stroke, wheel base, frame dimensions, length of springs and all that. And in all these things this car is the equal of any made.

And yet that wouldn't give you an adequate idea of just what this car is. Beyond the design, the steel, iron, wood and rubber, there is still a great something in this car which dimensions and materials cannot account for—an intimate, human quality. "It runs with eagerness."

People are all made of exactly the same materials. In general

People are all made of exactly the same materials. In general features they are all alike. Yet some are "different." There is some are "different." There is about some a something you can't explain by external terms—a personality, a superiority which rises from within, from reasons unexplained.

reasons unexplained.

A Chalmers "Forty" among automobiles has that rare quality. A quality of youth and life and unflagging energy. "It runs with eagerness."

A great many very particular people agree that there is no more beautiful car, either in line or finish than the Chalmers "Forty."

The price of \$2750 includes

The price of \$2750 includes Bosch magneto, Prest-O-Lite tank and gas lamps.

If you want high power, max-imum seating capacity and some of the final words in lines and finish, then you really should see this car.

Any Good Car a Good Investment

a Good Investment

There are many good cars made nowadays, and any good car is a good inrestinent. Yet we honeally believe
that Chalmers Cars offer the best value
that Chalmers Cars offer the best value
Compare them with others. Comparison has sold more Chalmers Cars than
all our advertising. If you can possibly
afford a motor car, don't put it of any
afford a motor car, don't put it of any
will be a Chalmers; but whether it is
or nnot, don't de, rive younelf and ur
family any longer of the pleasure that
by right is yours and theirs. There is
any in that will pay you cich a big
dividend in the saving of your health
car. A good thing is a better thing the
sooner you get it. Make your family
happy to-high by telling them that
you have made up your r of to get
se much about, namely, - a Chalmers

Chalmers Motor Company Detroit, Michigan